

# LIVING n o w



TRADITIONAL  
CONTROL



CONTROL WITH  
SMARTPHONE



VOICE  
COMMAND



PLANNING  
PROGRAMMED

**bticino**



# CONTENTS

DESIGN INNOVATION	6
NEW DIGITAL CONTROLS	8
FINISHES	10
THE SOLUTION FOR ALL SYSTEM REQUIREMENT	18
SMART ELECTRIC SYSTEM	20
HOME+CONTROL	24
INSTALLATION	30
HOME AUTOMATION THAT SPEAKS	36
HOME AUTOMATION LIKE NEVER TOUCHED BEFORE	38
INSTALLATION OF THE DIGITAL CONTROLS	42
ALWAYS PERFECT INSTALLATION	44
CATALOGUE	48

# LIVING n o w



Forever an icon,  
today Smart as well.

Living Now is the new Living generation. A timeless icon which combines the linearity of a unique design with the simplicity of Smart technology. All this without changing usual wiring procedures because Living Now is always installed in the traditional way, guaranteeing a perfect installation.



Traditional  
control




Control with  
smartphone



Voice  
command



Planning  
programmed



- **Innovative design:** revisited relationship between cover plate and functions.

- **Smart:** the first intrinsically connected wiring devices range!

- The best technical solutions for a **perfect** installation.



App  
Home + Control



## DESIGN INNOVATION

PERFECT PLANARITY AND  
ELEGANT DETAILS



Living Now, has won this prestigious international award confirming BTicino's ability to combine technology and design

**FULL TOUCH CONTROLS**  
The light can be switched on or off by pressing any point of the surface of the keys.  
After being pressed, the keys return to their original position, perfectly aligned.



**MORE SPACE FOR FUNCTIONS**  
Unique shape with space increased for functions

# NEW DIGITAL CONTROLS WITH LIVING NOW FINISH

Living Now series digital controls are now part of the MyHOME\_Up home automation range. A mix of incomparable innovation and simplicity, ready to be discovered, heard and touched.



## VOICE CONTROL

Device with built-in Amazon Alexa assistant, ideal for the voice control of the MyHOME\_Up home automation functions.



### **LIGHT AND FULL CONTROLS**

- New touch controls without cover plate
- Customised icons and leds using the app MyHOME\_Up
- Expandable to new functions

# DEVICE FINISHING

— WHITE



— SAND



— BLACK





### 3 COLOURS FOR THE DEVICES

The devices feature an aesthetic component, the covers, available in three different colours: white, sand and black. Satin finish surface: for a pleasant feel.

### COMBINATION WITH THE COVER PLATES

The Living Now cover plate range includes 16 finishes, purposely selected for use with the device covers, and made of different materials: techno polymer, metal and wood.



### COORDINATION OF APPEARANCE OF THE MYHOME\_UP DIGITAL CONTROLS

MyHOME\_Up digital controls do not require the use of cover plates and are available in white, sand and black.



# COVER PLATE FINISHING



**ICE cover plate**

Material: techno polymer  
Code: ...DW





The zamak and wood finishes are obtained using non-mass production procedures. The individual differences among the various cover plates are therefore a distinguishing valuable element.

**WHITE cover plate**

Material: techno polymer  
Code: ...KW

**GOLD cover plate**

Material: zamak  
Code: ...ZW

**MOON COVER PLATE**

Material: zamak  
Code: ...NW


**SKY cover plate**

Material: techno polymer  
Code: ...DA


**PIXEL cover plate**

Material: techno polymer  
- pixel effect  
Code: ...MW

# COVER PLATE FINISHING



**OAK cover plate**  
Material: wood  
Code: ...LM





The zamak and wood finishes are obtained using non-mass production procedures. The individual differences among the various cover plates are therefore a distinguishing valuable element.

**SAND cover plate**

Material: techno polymer  
Code: ...KM

**COPPER cover plate**

Material: zamak  
Code: ...ZM

**AURA cover plate**

Material: techno polymer  
Code: ...DM

**OPTIC cover plate**

Material: techno polymer  
- pixel effect  
Code: ...MM

# COVER PLATE FINISHING



## STEEL cover plate

Material: zamak  
Code: ...ZG





The zamak and wood finishes are obtained using non-mass production procedures. The individual differences among the various cover plates are therefore a distinguishing valuable element.

**BLACK cover plate**


Material: techno polymer  
Code: ...KG

**SPACE cover plate**

Material: zamak  
Code: ...NG

**WALNUT cover plate**

Material: wood  
Code: ...LG



**NIGHT cover plate**

Material: techno polymer  
Code: ...DG

THE RIGHT SOLUTION FOR ALL NEEDS

# SMART ELECTRICAL SYSTEM

Living Now WITH Netatmo



App HOME + CONTROL


## INSTALLATION WITH TRADITIONAL WIRING

Install a traditional electric system and add the SMART functions connected to the home Wi-Fi network, controlled using the HOME + CONTROL App.

### FUNCTIONS

- Lights
- Shutters
- Sockets
- Temperature control
- Scenario control
- Consumption display
- Load anti-blackout control
- Planning programmed


### CHOOSE HOW TO CONTROL IT





# HOME AUTOMATION SYSTEM

Living Now MyHOME\_Up



App MyHOME\_Up

## INSTALLATION WITH BUS

Create a BUS integrated system manageable from the MyHOME\_UP App, using your voice or the Touch Screen controls.

### FUNCTIONS

- Lights
- Shutters
- Sockets
- Temperature control
- Scenario control
- Consumption display
- Load anti-blackout control
- Video door entry system
- NUVO sound diffusion system
- Integration with other brand.


### CHOOSE HOW TO CONTROL IT



# SMART ELECTRICAL SYSTEM

Check your home just like your e-mail or your bank account. Starting from today, you will have all this at your fingertips, in full safety and easily.

App  
HOME + CONTROL




## GENERAL CONTROL

With one single click, a general control will allow you to switch off all the lights and lower all the shutters when you leave your home, or to activate your favourite scenario.



## CONTROL WITH SMARTPHONE

From your smartphone, you will be able to view and check the status of lights, shutters and connected power sockets from anywhere.



## VOICE COMMAND

You can control your system with your voice thanks to your favourite voice assistant.



## PLANNED PROGRAMMING

Program the activation of lights, shutters and loads connected to sockets based on your needs.

Some examples:

- automatically switch on the garden lights at sunset and switch them off at sunrise;
- switch on some lights and activate some shutters to simulate the presence of someone in the house when on holidays.

# Smart electric system

## MANAGEMENT OF THE TEMPERATURE

Remotely check and manage the temperature inside your home using your smartphone and installing the connected thermostat Smarter with Netatmo.



## LIGHTING AT THE DESIRED LEVEL

Adjust the light level for optimum personal comfort. You can do that from the connected Dimmer, the associated wireless controls and the Smartphone, using the Home+Control App.

**LOAD CONTROL TO AVOID BLACKOUTS (\*)**

In overload conditions, the system automatically disconnects the least important load to avoid tripping of the meter (blackout).

**ENERGY CONSUMPTION CONTROL**

Use your smartphone to check the electricity consumption of your appliances (daily, monthly and yearly).

**WIRELESS CONTROL**

You can add wireless controls (lights, shutters and sockets), or reposition them at any time depending on your needs.

**ALARM NOTIFICATIONS**

You can receive warning notifications on your smartphone.


# HOME + CONTROL

One single App, many connected advantages



Home+Control is the App that makes it simple to supervise all the Living Now Smart system functions using iOS and Android mobile devices, inside and outside the home.

The Homepage shows all the system information.



## WHAT YOUR CUSTOMER CAN DO:


1. Activate and customise **8 scenarios** (4 preconfigured scenarios, coming in, going out, day, night and 4 scenarios customisable by the user);
2. **Display and check the status of lights, shutters, loads connected to sockets and the room temperature;**
3. **Use the Smarter timer thermostat** simply and intuitively;
4. **Check the total home consumptions.**
5. **Receive notifications** on the load and system status;
6. **Define the load priority** for black-out prevention (function available by Autumn 2020).




## HOME + CONTROL

### CONFIGURATION IS EASY, BOTH FOR YOU AND YOUR CUSTOMER.


You simply have to download the App from the Apple or Google store, and follow the guided procedure.




Lights, shutters and generic loads activations



Consumption display



Management of the temperature



Scenario management




#### INTEGRATION WITH IFTTT

The Living Now Smart functions can be extended thanks to the integration with the IFTTT platform. It will be possible to create automated actions based on events generated in the electric system, or by external services and connected third-party devices.


«OK Google,  
set Kitchen light to 100%»

## YOUR CUSTOMERS CAN ALSO MANAGE THEIR HOME WITH THEIR VOICE

With Living Now with Netatmo, your customer will be able to control the system using Apple, Google and Amazon voice assistants. An extremely useful features, also for those with mobility problems.







Gateway for the connection of the system to the Internet  
through the Home Wi-Fi network.



“SIRI, switch the bedroom light on”,  
“OK Google, switch all the home lights off”,  
“ALEXA, set temperature to 20 degrees”.



Smart electrical system a simple, rational range of connected devices, both wired and wireless.

REMOTE CONNECTION	SCENARIOS
<p><b>CONNECTED DEVICES (230V A.C.)</b></p> <div style="display: flex; align-items: center; justify-content: center;">  </div> <p><b>Item K4500C</b> Gateway with Home/Away wireless switch</p> <div style="display: flex; align-items: center; justify-content: center;">  </div> <p><b>Item K4510C</b> Gateway with Home/Away wireless switch</p> <p><b>Item FC80GT</b> Gateway DIN</p>	
<p><b>BATTERY WIRELESS CONTROLS</b></p> <div style="display: flex; align-items: center; justify-content: center;">  </div> <div style="display: flex; justify-content: space-around;"> <div>  <p><b>Item K4570CW</b> Home/Away wireless switch</p> </div> <div>  <p><b>Item K4570CWI</b> Home/Away wireless switch</p> </div> <div>  <p><b>Item K4575CWI</b> 4 scenarios control</p> </div> <div>  <p><b>Item K4574CW</b> Night&amp;Day scenario control</p> </div> <div>  <p><b>Item K4574CWI</b> Night&amp;Day scenario control</p> </div> </div>	

LIGHTS	SHUTTERS	ENERGY AND CONSUMPTION MANAGEMENT
 <b>Item K4003C</b> Connected two-way switch	 <b>Item K4411C</b> Connected switch/dimmer	 <b>Item K4027C</b> Connected shutter control
 <b>Item FC80RC</b> Connected DIN relay 16 A	 <b>Item 3584C</b> Connected light relay 1,3 A	 <b>Item 4027C</b> Connected micromodule for shutter
 <b>Item K4003CW</b> Light control	 <b>Item K4003DCW</b> Double light control	 <b>Item F20T60A</b> Connected DIN meter
 <b>Item K4003CWI</b> Light control	 <b>Item 3585C</b> Motion sensor	 <b>Item K4027CWI</b> Shutter control
 <b>Item 3577C</b> Wireless module for mechanical switch	 <b>Item K4027CW</b> Shutter control	 <b>Item K4531C</b> Connected module for socket -16 A
		 <b>Item FC80GCS</b> Modulo DIN load management
		 <b>Item FC80CC</b> Connected DIN contactor 20 A
		 <b>Item 4141PC</b> Mobile german standard power outlet
		 <b>Item 4142PC</b> Mobile french/belgian standard power outlet
		 <b>Item XW8002</b> Connected thermostat
		 <b>Item XM8002</b> Item XM8002
		 <b>Item XG8002</b> Item XG8002
		 <b>Item XW8002</b> Connected thermostat


See catalogue for detailed descriptions, availability and full range of products.

# IT IS INSTALLED JUST LIKE A TRADITIONAL ELECTRIC SYSTEM


## 1.

### DEVICES ARE INSTALLED AND WIRED JUST LIKE TRADITIONAL DEVICES




In place of a traditional device, install the connected device of the corresponding type: one for each control line. Remember that the device must always be powered; therefore, ensure that the phase and neutral cables are present. Once installed, the connected control is already working; you will therefore be able to switch the connected light on without the need to do anything further.



EXAMPLE OF A REDIRECT LIGHT POINT






## 2.

**DEVICES CAN BE ASSOCIATED TO EACH OTHER BY SIMPLY PRESSING A PUSHBUTTON****A.** Power the electric system**B.** Press the In&Out master scenario control supplied with the gateway for 5 seconds**C.** Devices are associated automatically. You can already use the IN&Out scenario control for the activation of the general "Going Out" control

## 3.

**DOWNLOAD THE HOME+CONTROL APP FROM THE STORES AND FOLLOW THE GUIDED PROCEDURE TO DEFINE THE OBJECTS TO MANAGE**


App Home + Control

Scarica su  
App StoreDISPONIBILE SU  
Google Play**THE SYSTEM MAY BE EXPANDED WITH WIRELESS CONTROLS ASSOCIATED TO THE DEVICES BEING CONTROLLED****A.** Press the In&Out master scenario control supplied with the gateway for 5 seconds**B.** Place the devices to be associated in contact**C.** Install the wireless control anywhere you want, based on the needs of your customer




# The **new** connected thermostat **Smarther**

WITH  
**Netatmo**



## WITH THE APP IT'S ALL EASIER

- Remotely manage the thermostat simply and intuitively
- Create and modify the weekly programs
- Manage the thermostat from several smartphones and different users
- Control several thermostats in the same home or different homes
- Manage the thermostat updates
- Combine the voice command with your favorite voice assistant (Amazon Alexa, Apple Home Kit or Google Home)



# What can you do with the BTicino connected thermostat?



## SETTING THE PROGRAMS

Using the Home + Control App, it is possible to set preset programs based on your habits



## AWAY

If you need to be away from home for a few days you can, via the APP, act remotely to adjust the thermostat (e.g. in antifrost mode) independent of the automatic programming.



## BOOST

The Boost function can be used to activate the heating or cooling system for a limited time (30, 60 or 90 minutes), irrespective of the set program and the ambient temperature.



## MONITORING OF CONSUMPTIONS

Using the Home + Control App, it is possible to easily manage and monitor consumptions.



## MAXIMUM COMFORT IN EVERY ZONE

Using the same App, it is possible to manage several thermostats in the same home or in different homes, as well as set the desired temperature in every room for maximum comfort, thanks to the compatibility with Netatmo smart radiator valves.



 Netatmo

## The connected thermostat is simple and intuitive



Display the temperature and set it as desired



Display the set room temperature and humidity



Activate the Boost function



LOCAL DEVICE CONTROL



VOICE CONTROL




GEOLOCATION

# INSTALL A MyHOME\_Up SYSTEM USING THE LIVING NOW RANGE



Voice control



Light and Full digital controls

BUS



The range of home automation devices is completed by two innovative Living Now digital controls offering innovative control of your system:


- voice control with built-in Amazon Alexa voice assistant
- Light and Full digital controls.



App MyHOME\_Up



Display thermostat



Touch Screen HOMETOUCH (compatible with Netatmo cameras)



MyHOMEServer1


NUVO audio system

Third-party products and devices


Indoor and outdoor Netatmo cameras

## EVERYTHING UNDER CONTROL

Thanks to MyHOME\_Up, end users can manage their homes in full freedom: using Living Now manual controls, Touch Screen devices and Smartphones with the MyHOME\_Up App.



MyHOME\_Up system can be managed by voice through the Voice Control Alexa built-in and also with the Amazon and Google vocal assistants



# THE VOICE OF HOME AUTOMATION

## VOICE CONTROL: INNOVATIVE DEVICE WITH INTEGRATED AMAZON ALEXA VOICE ASSISTANT

Set each room of your home as you like with a voice control that controls the MyHOME\_Up system like never before.



**YOU ASK,  
ALEXA ANSWERS.**

Use your voice to activate the home automation functions of your home: lights, shutters, scenarios, favourite music, or ask for any other information.

Note: with the "Welcome me home" scenario, it is possible to activate lights and shutters and disable the burglar alarm.




Note: with the "Relax" scenario, it is possible to activate lights and shutters, set a comfort temperature and listen to the preferred music through the NUVO multi-room system.

# A NEW WAY TO TOUCH HOME AUTOMATION

## **LIGHT CONTROLS AND FULL CONTROLS: A MULTISENSORIAL EXPERIENCE**

- New touch controls without cover plate
- Customised icons and leds using the app MyHOME\_Up
- Light and Full controls expandable to new functions





App MyHOME\_Up

## CREATE CUSTOMISABLE FUNCTIONS

The function associated to the control device and the corresponding icon can be changed at any moment, also by the end user, using the app MyHOME\_Up.

### FUNCTION MODIFICATION



From dimmer control



To shutter control

### FUNCTION EXTENSION



From the control of one light



To the control of two lights



### LIGHT CONTROL

To manage the lighting  
(1 or 2 lights, group and general)

## CHOOSE BETWEEN FULL AND LIGHT CONTROLS

Digital controls for every need.

Two versions, endless customisation to be adapted to life style.




### FULL CONTROL

From 1 to 3 light, dimmer, rolling shutter, nuvo audio, load control and scenario.


## EXTEND THE CONTROL

Expand the system by adding new control devices with a new frame. Without wiring.

### FROM 3 CONTROL DEVICES



503E box




3 module-frame




Digital controls

### TO 4 CONTROL DEVICES



503E box



4 module-frame



Digital controls



**MOVE THE POSITION**

With a simple operation, it is possible to change the position of a control device, maintaining its function. Without wiring.




FROM THE LIVING ROOM



TO THE BEDROOM

# INSTALLATION OF DIGITAL CONTROLS




## FUNCTIONAL ELEMENTS

### INSTALLATION

With reference to the illustration, digital devices are installed in their respective flush mounted box and support, item K470..., using an appropriate "frame" with 27 Vd.c.control device power supply contacts.


The Module for connection to the system BUS and any flush mounted actuators are installed on the support.




## AESTHETIC ELEMENTS

### INSTALLATION OF VOICE CONTROL

This operation is completed in a similar way as the installation of digital controls, but it requires the removal of the two vertical finishing elements from the electrified frame.



# ALWAYS PERFECT INSTALLATION



## FUNCTIONAL ELEMENTS


### STANDARD INSTALLATION

Both in case of **traditional** and **connected devices**, installation is always standard, with the following characteristics:

- traditional wiring;
- flush mounted or plasterboard boxes, typically 2 to 6 modules;;
- no configuration required.

### YOUR WORK DOES NOT CHANGE, BUT IS MADE EASIER

The rules and procedures for the installation of the electric system don't change. Moreover, with the installation of the aesthetic components at the end of the works, you will hand to your customer a perfect and perfectly looking system.



## AESTHETIC ELEMENTS

### SITE ACTIVITY SEQUENCE

- Install the system, fully working, but without aesthetic elements (cover plates and covers)
- Protect the light point using the protective shell (supplied with the support)
- After completing all the works (including the painting of the walls), install the cover plates and the covers



### MORE ADVANTAGES

- When repainting the walls in the future, the customer will be able to easily remove the light point aesthetic components, cover plates and covers, and just as easily replace them on completion of the works
- After a few years the customer decides to change light points?  
It is possible to simply change the covers, without touching the mechanisms

# SOLUTIONS FOR AN ALWAYS PERFECT INSTALLATION

## FULL TOUCH CONTROL: ERGONOMICS

All the surface is functional. It can be precisely activated from the top, bottom or centre, ensuring exceptional ergonomics.



## FULL TOUCH CONTROL: ELECTRO MECHANICS


1) tested with over 80,000 activations with the load connected; double than the standard requirements.

This equals over 40 years of "normal" use.

2) 10AX 250 V or 15AX 127 V, tested up to 700 A peak; also perfect for the new LED light bulbs, which generate significant peak current when switched on.

## SELF CENTERING SYSTEM

This patented cover self-centering system ensures that the control covers are always aligned with the other components of the light point, even after extended use.



## FLOATING FRAME

It's the flexible floating frame at the back of the cover plate that makes sure that the light point perfectly adheres to any wall.

The floating frame gives the possibility of:

- 1) hiding wall defects;
- 2) hiding any irregularity in flush mounted boxes their positioning;
- 3) hiding the external collars of plasterboard boxes.



## STRONGER SUPPORT

Up to 4 times stronger than the current version, thanks to the new geometry and high performance materials.



## BETTER PROTECTION

The support has a protective shell, which can be used to protect supports and mechanisms from possible damage during decorating activities, for example when painting the walls.

## Traditional electrical system

### main controls



Devices to be completed with appropriate cover as indicated below

Item	Switch, two-way switch, pushbutton, intermediate switch 10 AX - 250 V~	Item	Cover
OK4001	1P 10 AX, 250 V~, 1-way switch, screw and plates terminals, lightable - 1 module	<input type="checkbox"/> KW01	<b>1 module</b> Lightable cover for item K4001, K4003, K4004, K4004L, K4004LB, K4004V127L, K4004V127LB, K4005, K4034, K4001A, K4003A, K4005A
OK4001A	1P 10 AX, 250 V~, 1-way switch, automatic terminals, lightable - 1 module	<input checked="" type="checkbox"/> KG01	
OK4001M2A	1P 10 AX, 250 V~, 1-way switch, automatic terminals, lightable - 2 modules	<input type="checkbox"/> KM01	
OK4003	1P 10 AX, 250 V~ 2-way switch, screw and plates terminals, lightable - 1 module	<input type="checkbox"/> KW01M2	<b>2 modules</b> Lightable cover for item K4001, K4003, K4004, K4004L, K4004LB, K4004V127L, K4004V127LB, K4005, K4034, K4001A, K4003A, K4005A, K4001M2A, K4003M2A, K4005M2A
OK4003A	1P 10 AX, 250 V~ 2-ways switch, automatic terminals, lightable - 1 module	<input checked="" type="checkbox"/> KG01M2	
OK4003M2A	1P 10 AX, 250 V~, 2-ways switch, automatic terminals, lightable - 2 modules	<input type="checkbox"/> KM01M2	
OK4004	* 1P 10 AX, 250 V~ 4-way switch, screw and plates terminals - 1 module	<input type="checkbox"/> KW01X	<b>Covers with symbols for controls</b>
OK4004L	* 1P 10 AX, 250 V~ LIT 4-ways switch, screw and plates terminals, with white LED for backlighting (the LED is not interchangeable) - 1 module	<input checked="" type="checkbox"/> KG01X	<b>1 module - high brightness</b>
OK4004LB	* 1P 10 AX, 250 V~ LIT 4-ways switch, screw and plates terminals, with blue LED for backlighting (the LED is not interchangeable) - 1 module	<input type="checkbox"/> KM01X	Lightable cover for item K4001, K4003, K4004, K4004L, K4004LB, K4004V127L, K4004V127LB, K4005, K4034, K4001A, K4003A, K4005A, K4001M2A, K4003M2A, K4005M2A
OK4004V127L	* 1P 10 AX, 127 V~ LIT 4-way switch, screw and plates terminals, with white LED for backlighting (the LED is not interchangeable) - 1 module	<input type="checkbox"/> KW01M2X	<b>2 modules - high brightness</b>
OK4004V127LB	* 1P 10 AX, 127 V~ LIT 4-way switch, screw and plates terminals, with blue LED for backlighting (the LED is not interchangeable) - 1 module	<input checked="" type="checkbox"/> KG01M2X	Lightable cover for item K4001, K4003, K4004, K4004L, K4004LB, K4004V127L, K4004V127LB, K4005, K4034, K4001A, K4003A, K4005A, K4001M2A, K4003M2A, K4005M2A
OK4005	1P (NO) 10 A, 250 V~ pushbutton, screw and plates terminal, lightable - 1 module	<input type="checkbox"/> KM01M2X	<b>1 module - light symbol</b>
OK4005A	1P (NO) 10 A, 250 V~ pushbutton, automatic terminals, lightable - 1 module	<input type="checkbox"/> KW01A	Lightable cover for item K4001, K4003, K4004, K4004L, K4004LB, K4004V127L, K4004V127LB, K4005, K4034, K4001A, K4003A, K4005A, K4001M2A, K4003M2A, K4005M2A
OK4005M2A	1P (NO) 10 A, 250 V~ pushbutton, automatic terminals, lightable - 2 modules	<input checked="" type="checkbox"/> KG01A	<b>2 modules - light symbol</b>
		<input type="checkbox"/> KM01A	Lightable cover for item K4001, K4003, K4004, K4004L, K4004LB, K4004V127L, K4004V127LB, K4005, K4034, K4001A, K4003A, K4005A, K4001M2A, K4003M2A, K4005M2A
		<input type="checkbox"/> KW01D	<b>1 module - bell symbol</b>
		<input checked="" type="checkbox"/> KG01D	Lightable cover for item K4001, K4003, K4004, K4004L, K4004LB, K4004V127L, K4004V127LB, K4005, K4034, K4001A, K4003A, K4005A, K4001M2A, K4003M2A, K4005M2A
		<input type="checkbox"/> KM01D	
		<input type="checkbox"/> KW01M2D	<b>2 modules - bell symbol</b>
		<input checked="" type="checkbox"/> KG01M2D	Lightable cover for item K4001, K4003, K4004, K4004L, K4004LB, K4004V127L, K4004V127LB, K4005, K4034, K4001A, K4003A, K4005A, K4001M2A, K4003M2A, K4005M2A
		<input type="checkbox"/> KM01M2D	
		<input type="checkbox"/> KW01F	<b>1 module - key symbol</b>
		<input checked="" type="checkbox"/> KG01F	Lightable cover for item K4001, K4003, K4004, K4004L, K4004LB, K4004V127L, K4004V127LB, K4005, K4034, K4001A, K4003A, K4005A, K4001M2A, K4003M2A, K4005M2A
		<input type="checkbox"/> KM01F	
		<input type="checkbox"/> KW01M2F	<b>2 modules - key symbol</b>
		<input checked="" type="checkbox"/> KG01M2F	Lightable cover for item K4001, K4003, K4004, K4004L, K4004LB, K4004V127L, K4004V127LB, K4005, K4034, K4001A, K4003A, K4005A, K4001M2A, K4003M2A, K4005M2A
		<input type="checkbox"/> KM01M2F	

#### Notes:

- for the LEDs to use see the "Backlighting LEDs" section later on in the catalogue.
- for solutions requiring 2-module covers for the main controls, it will be necessary to install two "half-module blanking modules" (item K4949) at the sides of the control, see example on page 105.

White colour cover

Black colour cover

Sand colour cover

Neutral item (without cover)

Items in red colour: New products



## Living Now with Netatmo smart electrical system

main controls



Devices to be completed with appropriate cover as indicated below


Item	Connected switches and light relay	Item	Cover
OK4001C	<b>Connected switches and light relay</b>  Connected 1-way switch. It controls the lights locally or remotely. It can be installed like a traditional two-way switch and is compatible with all loads with max. power 250 W. It has a blue LED, which can be configured using the Home + Control App for the localisation and load status functions. It can be associated to one or more wireless controls. Caution: neutral connection is necessary. Power supply 110-230 V~ - 1 module		<b>1 module</b> <input type="checkbox"/> KW01 <input checked="" type="checkbox"/> KG01 <input type="checkbox"/> KM01
OK4003C	Connected 2-ways switch. It allows to control lights locally or remotely. The connected 2ways switch has the same installation and usability of a traditional 2ways switch and it is compatible with all loads with max power 250 W. It's equipped with a blue LED light used always on for localization modality or on, when the light is on for the load status modality. It can be associated with "wireless light switches". Caution: Must be connected to the neutral. Power supply 110-230 V~ - 1 module		<b>2 modules</b> <input type="checkbox"/> KW01M2 <input checked="" type="checkbox"/> KG01M2 <input type="checkbox"/> KM01M2
O 3584C	Connected lighting micromodule. It allows to control lights locally or remotely. It is compatible with all loads with max power 300 W. It can be connected to one or more traditional push-button or associated with "wireless light switches". It is installed as a traditional relay in the box (behind the button) or in derivation boxes. Caution: Must be connected to the neutral. Power supply 110-230 V~		 Lightable covers for items K4001C and K4003C
O FC80RC	DIN switchboard light device for loads with absorption In= 16 A. Equipped with a meter measuring the current absorbed by the load and contacts for control with up to 10 pushbuttons. 1 DIN module. Power supply 110-230 V~		 Lightable covers for items K4001C and K4003C

Note: for the use of the connected devices, the gateway, item **K4500C**, **K4510C** or **FC80GT** must be installed as part of the system.


If the gateway is connected to the internet through the Wi-Fi network, it will be possible to manage the system from the home using the specific **HOME + CONTROL** App



Three-point lighting control with connected two-way switch, item K4003C, installed instead of a traditional two-way switch



Three-point lighting control with pushbuttons and connected lighting micromodule, item 3584C, installed instead of a traditional relay



White colour cover

Black colour cover

Sand colour cover

Neutral item (without cover)

Items in red colour: New products

## Traditional electrical system control for shutters



Devices to be completed with appropriate cover as indicated below

Item	Switch	Cover
○ K4027		<b>1 module</b> <input type="checkbox"/> KW06 <input checked="" type="checkbox"/> KG06 <input type="checkbox"/> KM06  <input type="checkbox"/> KW06V <input checked="" type="checkbox"/> KG06V <input type="checkbox"/> KM06V  <input type="checkbox"/> KW05L <input checked="" type="checkbox"/> KG05L <input type="checkbox"/> KM05L  <input type="checkbox"/> KW05 <input checked="" type="checkbox"/> KG05 <input type="checkbox"/> KM05  <input type="checkbox"/> KW05V <input checked="" type="checkbox"/> KG05V <input type="checkbox"/> KM05V
○ K4036		<b>1 module</b> <input type="checkbox"/> KW06 <input checked="" type="checkbox"/> KG06 <input type="checkbox"/> KM06  <input type="checkbox"/> KW06V <input checked="" type="checkbox"/> KG06V <input type="checkbox"/> KM06V  <input type="checkbox"/> KW05L <input checked="" type="checkbox"/> KG05L <input type="checkbox"/> KM05L  <input type="checkbox"/> KW05 <input checked="" type="checkbox"/> KG05 <input type="checkbox"/> KM05  <input type="checkbox"/> KW05V <input checked="" type="checkbox"/> KG05V <input type="checkbox"/> KM05V
○ K4037		<b>1 module</b> <input type="checkbox"/> KW06M2 <input checked="" type="checkbox"/> KG06M2 <input type="checkbox"/> KM06M2  <input type="checkbox"/> KW05M2 <input checked="" type="checkbox"/> KG05M2 <input type="checkbox"/> KM05M2  <input type="checkbox"/> KW06M2V <input checked="" type="checkbox"/> KG06M2V <input type="checkbox"/> KM06M2V  <input type="checkbox"/> KW05M2V <input checked="" type="checkbox"/> KG05M2V <input type="checkbox"/> KM05M2V

**White** colour cover

**Black** colour cover

**Sand** colour cover

○ Neutral item (without cover)

Items in red colour: New products




## Living Now with Netatmo smart electrical system

control for shutters



Devices to be completed with appropriate cover as indicated below

Item	Connected devices for shutters	Item	Cover
OK4027C	<p>Connected rolling shutter switch - It allows the control of a shutter locally or remotely. Compatible with all standard rolling shutter motors (with a mechanical or electromechanical stop and max power 500 VA) controlled by a wired shutter switch (switching of the same motor power supply). Not compatible with motors for radio-controlled or pulse-controlled roller shutters. It can be associated with one or more wireless commands. Caution: Must be connected to the neutral. Power supply 110-230 V~ - 1 module</p>		<b>1 module</b> <input type="checkbox"/> KW32 <input checked="" type="checkbox"/> KG32 <input type="checkbox"/> KM32
OK4027CIL	<p>As above - interlocked modality</p>		<b>2 modules</b> <input type="checkbox"/> KW32M2 <input checked="" type="checkbox"/> KG32M2 <input type="checkbox"/> KM32M2
OK4027CM2	<p>As K4027C - 2 modules</p>		
O4027C	<p>Connected micromodule for shutters. Associated to one or more shutter wireless controls, it controls a shutter locally or remotely. Compatible with all standard shutter motors (with mechanical or electronic limit switch and maximum power 500 VA), controlled by a wired shutter changeover switch (changeover with the same power supply as the motor). Not compatible with radio controlled or pulse controlled shutter motors. It can be installed in the existing shutter box with no need of masonry works. Power supply 110-230 V~</p>		



For correct operation, connect also the neutral conductor to the connected devices.

Note: for the use of the connected devices, the gateway, item **K4500C**, **K4510C** or **FC80GT** must be installed as part of the system.

If the gateway is connected to the internet through the Wi-Fi network, it will be possible to manage the system from the home using the specific **HOME + CONTROL** App



White colour cover

Black colour cover

Sand colour cover

Neutral item (without cover)

Items in red colour: New products

## Traditional electrical system

### dimmer



K4411



K4410



KW19



KG19



KM19

Devices to be completed with appropriate cover as indicated below

Item	Dimmer	Item	Cover
OK4411	<b>Universal dimmer</b> Universal pushbutton dimmer - resistive/inductive/ capacitive/fluorescent/compact/ dimmer LED. 100 to 240 V~ 50 ÷ 60 Hz - connection without neutral - 2 modules	<b>1 module</b> KW19 KG19 KM19	Cover for item K4411, K4410
OK4410	<b>Dimmer for ballast lamp</b> Pushbutton dimmer for ballast lamp with 0-10V output. 100 to 240 V~ 50 to 60 Hz - 2 modules		

### DIMMER K4410 - LOADS MANAGED TABLE

		1 - 10 V		
	+35°C 0°C 2x2,5mm <sup>2</sup> 100-240 V~ 50/60 Hz			
240 V	Max.	600 VA	600 VA	600 VA
	Min.	20 VA	20 VA	20 VA
100 V	Max.	300 VA	300 VA	300 VA
	Min.	20 VA	20 VA	20 VA

### DIMMER K4411 - LOADS MANAGED TABLE

		R	L	C/L		
	+35°C 0°C 100- 240 V~ 50/60 Hz 2 x 2.5 mm <sup>2</sup>					
240 V	Max.	400 W	400 W	400 VA	400 VA	200 VA
	Min.	3 W	3 W	3 VA	3 VA	3 VA
100 V	Max.	200 W	200 W	200 VA	200 VA	100 VA
	Min.	3 W	3 W	3 VA	3 VA	3 VA

**White** colour cover

**Black** colour cover

**Sand** colour cover

**Neutral item (without cover)**

Items in red colour: New products



## Living Now with Netatmo smart electrical system



K4411C

K4411CM2



Devices to be completed with appropriate cover as indicated below


Item	Connected Dimmer/Switch	Cover
OK4411C	<p><b>Universal dimmer</b></p> <p>Dimmer/switch. It allows to control lights locally or remotely, with the dimmer functionality that can be activated from APP Home+Control. It has the same installation and usability of a traditional switch and it is compatible with all loads (LED, halogen) with max power 150 W at 230 V (or 75 W at 110 V). It's equipped with a blue LED light used for localization modality or load status modality, configurable by APP. It can be connected to one or more traditional push-button or associated with "wireless light switches". Caution: Must be connected to the neutral. Power supply 110-230 V~ - 1 module</p>	<p><input type="checkbox"/> KW33  <input checked="" type="checkbox"/> KG33  <input type="checkbox"/> KM33</p>
OK4411CM2	<p>Dimmer/switch without neutral. It allows to control lights locally or remotely, with the dimmer functionality that can be activated from APP Home+Control. It has the same installation and usability of a traditional switch and it is compatible with all loads (LED, halogen) with power 5-300 W at 230 V. It's equipped with a blue LED light used for localization modality or load status modality, configurable by APP. It can be connected associated with "wireless light switches". It doesn't require connection to the neutral, it comes with an active compensator. Power supply 110-230 V~ - 2 modules</p>	<p><input type="checkbox"/> KW33M2  <input checked="" type="checkbox"/> KG33M2  <input type="checkbox"/> KM33M2</p>

Note: for the use of the connected devices, the gateway, item **K4500C**, **K4510C** or **FC80GT** must be installed as part of the system.

If the gateway is connected to the internet through the Wi-Fi network, it will be possible to manage the system from the home using the specific **HOME + CONTROL** App



Dimmer/switch item K4027C with remote pushbuttons



White colour cover

Black colour cover

Sand colour cover

Neutral item (without cover)

Items in red colour: New products

## Traditional electrical system two-pole switches



KW4002      KG4002      KM4002



KW02      KG02      KM02

Devices to be completed with appropriate cover as indicated below

Item	Switches	Cover
<input type="checkbox"/> KW4002 <input checked="" type="checkbox"/> KG4002 <input type="checkbox"/> KM4002	<b>Switches</b>  2P 16 AX, 250 V~, lightable switch - 1 module	<b>Cover</b> <b>1 module</b> <input type="checkbox"/> KW02 <input checked="" type="checkbox"/> KG02 <input type="checkbox"/> KM02   Cover for item KW4002 Cover for item KG4002 Cover for item KM4002

 **White** colour cover **Black** colour cover **Sand** colour cover Neutral item (without cover)

Items in red colour: New products

## Traditional electrical system

### other pushbuttons



Devices to be completed with appropriate cover as indicated below

Item	Pushbutton
O K4034	10 A 250 V~ opening pushbutton 1 P (NO) and 1 P (NC), lightable - 1 module

Pull cord pushbutton	
<input type="checkbox"/> KW4033	10 A 250 V~ pull-cord pushbutton 1 P (NO) and 1 P (NC) - 1 module

Plate pushbutton	
OK4040	3 A 250 V~ door pushbutton - backlit with LED technology (already installed), cover supplied in package with the pushbutton - 2 modules
OK4040V12	Door pushbutton as above - 12 V~

Item	Cover for pushbutton
<input type="checkbox"/> KW01 <input checked="" type="checkbox"/> KG01 <input type="checkbox"/> KM01	<b>1 module</b> Cover lightable for item K4034

Cover for pull cord pushbutton	
<input type="checkbox"/> KW02 <input checked="" type="checkbox"/> KG02 <input type="checkbox"/> KM02	<b>1 module</b> Cover for item KW4033 Cover for item KG4033 Cover for item KM4033

White colour cover

Black colour cover

Sand colour cover

Neutral item (without cover)

Items in red colour: New products

## Traditional electrical system

### IR switches



K4431                    K4432                    K4430



Devices to be completed with appropriate cover as indicated below

Item	IR switches	Item	Cover
OK4431	<p>Switch with passive infrared ray movement sensor, suitable for all types of load including LED lamps - 3 wires - variable-threshold twilight circuit with possibility of exclusion - timing circuit to delay switching off adjustable from 30 seconds to 10 minutes - 230 V~ power supply - 1 module</p> <p><b>Note:</b> for further information, see the technical section at the end of the Catalogue</p>	<input type="checkbox"/> KW16 <input checked="" type="checkbox"/> KG16 <input type="checkbox"/> KM16	<b>1 module</b>  Cover for item K4431
OK4432	<p>Switch with passive infrared ray movement sensor, suitable for all types of load including LED lamps - 3 wires - variable-threshold twilight circuit with possibility of exclusion - timing circuit to delay switching off adjustable from 10 seconds to 10 minutes - 230 V~ power supply - 2 modules</p> <p><b>Note:</b> for further information, see the technical section at the end of the Catalogue</p>	<input type="checkbox"/> KW17 <input checked="" type="checkbox"/> KG17 <input type="checkbox"/> KM17	<b>2 modules</b>  Cover for item K4432, K4430
OK4430	<p>switch with passive infrared ray movement sensor, suitable for all types of load including LED lamps - 2 wires - variable-threshold twilight circuit with possibility of exclusion - timing circuit to delay switching off adjustable from 10 seconds to 10 minutes - it has a selector switch for operating type ON - AUTO - OFF. It is possible to choose between two types of configuration:</p> <ol style="list-style-type: none"> <li>1) visible selector switch (install the selector switch supplied and use the cover item. ...17SL)</li> <li>2) hidden selector switch (do not install the selector switch supplied and use the cover item ...17) - power supply 230 V~ - 2 modules</li> </ol> <p><b>Note:</b> for further information, see the technical section at the end of the Catalogue.</p>	<input type="checkbox"/> KW17SL <input checked="" type="checkbox"/> KG17SL <input type="checkbox"/> KM17SL	 Cover for item K4430

- **Note:** use item K4430 with ..17 or ..17SL covers
- cover ..17SL: cover providing direct access to the selector. The device operating mode can be changed at any time as the selector is always exposed.
- cover ..17: cover not providing access to the selector. To change the operating mode using the selector on the product, it will be necessary to remove the cover

**White** colour cover

**Black** colour cover

**Sand** colour cover

**Neutral item (without cover)**

Items in red colour: New products


**Living Now with Netatmo smart electrical system**

 **IR switch**  
eliot™



3585C


Item	Motion sensor wireless
O 3585C	 It controls one or more devices connected for light control. Infrared detection with angle of 140°. Distance of the adjustable sensor from 2 to 8 m. Switch off delay with 1 to 30 min adjustable delay time and 1 to 1000 lux brightness threshold. Test possible with a 5 sec. delay Recommended assembly height: 2.5 m. Optimum distance between 2 detectors: 6 m. For indoor and outdoor use (IP44). Supplied with 2 1.5V AA batteries for power supply.

Note: for the use of the connected devices, the gateway, item **K4500C**, **K4510C** or **FC80GT** must be installed as part of the system.

If the gateway is connected to the internet through the Wi-Fi network, it will be possible to manage the system from the home using the specific **HOME + CONTROL** App



HOME + CONTROL



**White** colour cover

**Black** colour cover

**Sand** colour cover

Neutral item (without cover)

Items in red colour: New products

## Traditional electrical system thermostats



KW4441



KG4441



KM4441

Item
<input type="checkbox"/> KW4441
<input checked="" type="checkbox"/> KG4441
<input type="checkbox"/> KM4441

### Electronic thermostats



Electronic room thermostat - relay output with  
1 contact in switching free of 5(2)A potential.  
- power supply 230 V~ - 2 modules

**White** colour cover

**Black** colour cover

**Sand** colour cover

Neutral item (without cover)

Items in red colour: New products


**Living Now with Netatmo smart electrical system**

thermostats

eliot™



XW8002



XG8002



XM8002



XW8002W

The Smarter with Netatmo connected thermostat, together with the dedicated HOME+CONTROL APP, is a device which allows you to adjust and monitor the temperature in the rooms precisely and accurately; all the programming and most of the functions are performed simply and intuitively using the APP. Thanks to its Wi-Fi connection, Smarter with Netatmo can be programmed and controlled remotely; it can also display the temperature and humidity measured in the room. The temperature level can be set locally for manual operation and the Boost mode can be activated. The Boost forces the switching on of the system for a limited time (30, 60 or 90 minutes) independent of the measured and programmed temperature.

It's also possible to set a different temperature in each room of the house for the maximum comfort, thanks to its compatibility with Netatmo smart radiator valves.

Smarter with Netatmo can also be controlled with Google, Amazon Alexa and Apple Home Kit voice assistants.

**Features:**

- 110 ÷ 230 V~, 50/60 Hz power supply;
- 2 W max absorption;
- maximum cable section 1 x 1.5mm<sup>2</sup>;
- temperature measurement 5 ÷ 40°C;
- temperature set-point 5 ÷ 40°C;
- increase of 0.5°C;
- 1-contact output in switching free of potential 5(2)A.

**Types of installation:**

- flush mounted, on boxes item 503E or 500 (for item 500 use the wall dowels)
- plasterboard, on boxes 2 module and 3 module

It is available in three colours: white (XW8002), sand (XM8002) and black (XG8002).

Item	Connected thermostats
□ XW8002	White
■ XG8002	Black
□ XM8002	Sand
XW8002W	 Features: as XW8002. Installation on the wall, using screws and dowels suitable for the installation surface (brickwork, plasterboard, tiles etc.). It is only available in white.

**Connected thermostats**

 White  
Black  
Sand

 Features: as XW8002.  
Installation on the wall, using screws and dowels suitable for the installation surface (brickwork, plasterboard, tiles etc.).  
It is only available in white.

**App HOME + CONTROL for management of connected devices**


□ White colour cover

■ Black colour cover

□ Sand colour cover

○ Neutral item (without cover)

Items in red colour: New products

## Traditional electrical system

### italian standard sockets



Devices to be completed with appropriate cover as indicated below

Item	Italian standard sockets	Cover
	<b>Italian standard sockets</b>	
<input type="checkbox"/> KW4113	2 P+E 10 A , 250 V~ socket - centre distance 19 mm - shielded tulip contacts ø 4 mm - 1 module	<input type="checkbox"/> KW02
<input checked="" type="checkbox"/> KG4113		<input checked="" type="checkbox"/> KG02
<input type="checkbox"/> KM4113		<input type="checkbox"/> KM02
<input checked="" type="checkbox"/> KR4113		<input checked="" type="checkbox"/> KR02
<input type="checkbox"/> KW4180	 White	 Cover for item KW4113, KW4180
<input checked="" type="checkbox"/> KG4180	 Black	Cover for item KG4113, KG4180
<input type="checkbox"/> KM4180	 Sand	Cover for item KM4113, KM4180
<input checked="" type="checkbox"/> KR4180	 Red	Cover for item KR4113, KR4180
	Socket 2 P+E 16 A 250 V a.c. - centre distance 19 mm and 26 mm - shielded tulip contacts - for 2 P and 2 P+E 10 and 16 A plugs - 1 module	
<input type="checkbox"/> KW4180	 White	
<input checked="" type="checkbox"/> KG4180	 Black	
<input type="checkbox"/> KM4180	 Sand	
<input checked="" type="checkbox"/> KR4180	 Red	
		<b>1 module</b>
		 Cover for item KW4113, KW4180
		Cover for item KG4113, KG4180
		Cover for item KM4113, KM4180
		Cover for item KR4113, KR4180

**White** colour cover

**Black** colour cover

**Sand** colour cover

Neutral item (without cover)

Items in red colour: New products



# Living Now with Netatmo smart electrical system

connected devices for energy management



Devices to be completed with appropriate cover as indicated below

Item	Connected devices for energy management	Connected socket	Cover
OK4531C	 <p>Connected socket module - wiring to a power outlet, allows to remotely control appliances and check the consumption (instantaneous, daily, monthly). It is also possible to receive notifications in case of anomalous consumption. The connected socket module is compatible with any device electric and large appliances up to 16 A 3680 W max. (protected against overloads). It is equipped with a LED light lit in blue when it is on. This option can be enabled or disabled in the "Home+Control" app. It can be associated with "wireless light switches". Power supply 110-230 V~ - 1 module</p>	<input type="checkbox"/> KW4141AC <input checked="" type="checkbox"/> KG4141AC <input type="checkbox"/> KM4141AC	 <p>2P+E 16 A 250 V a.c. German standard connected socket. It allows remote control of electric devices and also to monitor their consumption (instantaneous, daily, monthly). It is also possible to receive notifications that can be configured. Compatible with all the electric devices with power up to 16 A 3680W (with overload protection). Integrated with a 2-module support, it can be installed instead of an existing socket in a 40 mm deep box. Screw fixing and connection using automatic clamps. It has a blue LED that lights up when the socket is ON and that can be configured by means of the Home + Control APP. It can be associated to one or more wireless light controls. Power supply 110-230 V~</p>
O4141PC	 <p>Mobile connected power outlet. Directly connected to an existing socket, it allows remote control of all the connected electrical appliances. It also monitors the instantaneous, daily and monthly consumption. Compatible with all the devices with power up to 16 A 3680 W (with overload protection). It can be associated to wireless light controls. Power supply 110-230 V~</p>	<input type="checkbox"/> KW4142AC <input checked="" type="checkbox"/> KG4142AC <input type="checkbox"/> KM4142AC	 <p>As above French/belgian standard socket</p>
O4142PC	 <p>As above French/belgian standard socket</p>	<input type="checkbox"/> KW31 <input checked="" type="checkbox"/> KG31 <input type="checkbox"/> KM31	 <p>Cover for item K4531C</p>
FC80CC	 <p>Connected contactor for single-phase and/or three-phase loads with maximum absorption In= 20 A. With meter for the measurement of the current absorbed by the load. Power supply 110-230 V~ - 1 DIN module</p>	<input type="checkbox"/> KW34M2 <input checked="" type="checkbox"/> KG34M2 <input type="checkbox"/> KM34M2	 <p>Cover for item KW4141AC Cover for item KG4141AC Cover for item KM4141AC</p>
OFC80GCS	 <p>Connected DIN load management module for the monitoring of the consumptions of the whole electric system, the powering or disconnection of the loads, and the setting of scenarios with priority or non-priority loads. When the maximum intended power is reached, the non-priority loads are temporarily disconnected to avoid black-outs. A toroid for the current reading is provided. Power supply 110-230 V~ - 1 DIN module</p>	<input type="checkbox"/> KW35M2 <input checked="" type="checkbox"/> KG35M2 <input type="checkbox"/> KM35M2	 <p>Cover for item KW4142AC Cover for item KG4142AC Cover for item KM4142AC</p>
F20T60A	 <p>Connected DIN meter. It allows to measure the energy consumption of the house electric installation (instantaneous, daily, monthly). It is also possible to receive notifications in case of exceeded the maximum power provided by your contract to avoid possible black-out. A toroid is provided to read the current. Power supply 110-230 V~ - 1 DIN module</p>		

White colour cover

Black colour cover

Sand colour cover

Neutral item (without cover)

Items in red colour: New products



Devices to be completed with appropriate cover as indicated below

Item	Gateway with socket	Item	Cover required for the gateway with socket
<input type="checkbox"/> KW4501C <input checked="" type="checkbox"/> KG4501C <input type="checkbox"/> KM4501C	<b>Gateway with socket</b>  German standard socket. The gateway creates a connected installation in the home. It can be used to control lights, shutters, and electric appliances plugged into connected sockets: - using the smartphone and the Home + Control app - using the voice assistants - from the general control at the home entrance. It integrates a 2P+E 16 A 250 V~ German standard connected socket for the remote control of electric devices and to monitor their consumption (instantaneous, daily, monthly). Compatible with all the electric devices with power up to 16 A 3680W (with overload protection). It can be installed instead of an existing socket in a 40 mm deep box. Screw fixing and connection using automatic clamps It has a blue LED that lights up when the socket is ON and that can be configured by means of the Home + Control APP. It can be associated to one or more wireless light controls. It is also supplied with wireless master IN&OUT scenario control, required for the association of all connected devices. Power supply 110-230 V~	<input type="checkbox"/> KW51 <input checked="" type="checkbox"/> KG51 <input type="checkbox"/> KM51	<b>2 modules</b>  Cover required for all the gateways with sockets, in addition to the 2 modules cover for the socket part
<input type="checkbox"/> KW4502C <input checked="" type="checkbox"/> KG4502C <input type="checkbox"/> KM4502C	 As above French/belgian standard socket	<input type="checkbox"/> KW34M2 <input checked="" type="checkbox"/> KG34M2 <input type="checkbox"/> KM34M2	<b>Cover for the socket</b> <b>2 modules</b>  Cover for item KW4501C Cover for item KG4501C Cover for item KM4501C
		<input type="checkbox"/> KW35M2 <input checked="" type="checkbox"/> KG35M2 <input type="checkbox"/> KM35M2	 Cover for item KW4502C Cover for item KG4502C Cover for item KM4502C

#### EXAMPLE: FUNCTION, COVER PLATE & COVER COLOUR CHOICE



## Traditional electrical system

italian/german and german standard sockets



KW4140A16



KG4140A16



KG4140A16F



KR4140A16F



KW03



KG03



KM03



KW03M3



KW411



KG411



KM411



KV411



KG04



KG04P



KW04P



KM04M3

Devices to be completed with appropriate cover as indicated below

Item	Italian/german standard sockets
<input type="checkbox"/> KW4140A16	
<input checked="" type="checkbox"/> KG4140A16	Socket 2 P+E 16 A 250 V~ - 19 and 26 mm centre distance in 2-centre configuration - protected tulip contacts; side earth contact for German standard plugs; suitable for: Italian standard plugs 2P and 2 P+E 10/16 A, and 16A, German standard plugs 2P+E 16 A - 2 modules.
<input type="checkbox"/> KM4140A16	
<input checked="" type="checkbox"/> KR4140A16	
<input type="checkbox"/> KW4140A16F	
<input checked="" type="checkbox"/> KG4140A16F	German and Italian standard flat socket. When the plug is inserted the socket surface slides inside the casing; it returns to its initial position when the plug is taken out. Socket 2 P+E 16 A 250 V~ - 19 mm and 26 mm centre distance in 2-centre configuration - protected tulip contacts; side earth contact for German standard plugs; suitable for: Italian standard plugs 2P and 2 P+E 10/16 A, and 16A, German standard plugs 2P+E 16 A. - cannot be backlit - 2 modules
<input type="checkbox"/> KM4140A16F	
<input checked="" type="checkbox"/> KR4140A16F	

### German standard sockets

<input type="checkbox"/> KW4141	
<input checked="" type="checkbox"/> KG4141	
<input type="checkbox"/> KM4141	
<input checked="" type="checkbox"/> KR4141	
<input checked="" type="checkbox"/> KV4141	
<input type="checkbox"/> KW4141A	
<input checked="" type="checkbox"/> KG4141A	
<input type="checkbox"/> KM4141A	

German standard socket 2 P+E 16 A 250 V~ socket with earth side contacts - shielded tulip contacts - with screw terminals

As above - automatic clamps

Item	Cover for italian/german standard sockets
<input type="checkbox"/> KW03	
<input checked="" type="checkbox"/> KG03	Cover suitable for italian/german standard sockets.
<input type="checkbox"/> KM03	
<input checked="" type="checkbox"/> KR03	
<input type="checkbox"/> KW03M3	
<input checked="" type="checkbox"/> KG03M3	Cover suitable for italian/german standard sockets
<input type="checkbox"/> KM03M3	

### Cover for german standard sockets

Item	Cover for german standard sockets
<input type="checkbox"/> KW04	
<input checked="" type="checkbox"/> KG04	Cover suitable for german standard sockets
<input type="checkbox"/> KM04	
<input checked="" type="checkbox"/> KR04	
<input checked="" type="checkbox"/> KV04	
<input type="checkbox"/> KW04P	
<input checked="" type="checkbox"/> KG04P	Cover suitable for german standard sockets
<input type="checkbox"/> KM04P	
<input type="checkbox"/> KW04M3	
<input checked="" type="checkbox"/> KG04M3	Cover suitable for german standard sockets
<input type="checkbox"/> KM04M3	

White colour cover

Black colour cover

Sand colour cover

Neutral item (without cover)

Items in red colour: New products

## Traditional electrical system

### European/american standard sockets



Devices to be completed with appropriate cover as indicated below

Item	European/american standard sockets	Item	Cover for european/american standard sockets
<input type="checkbox"/> KW4125	Euro american standard 2 P 16 A 127/250 V~ socket	<input type="checkbox"/> KW51	Cover suitable for all the items over described
<input checked="" type="checkbox"/> KG4125	- Ø 5 mm shielded tulip contacts - 2 modules	<input type="checkbox"/> KG51	
<input type="checkbox"/> KM4125		<input type="checkbox"/> KM51	
<input type="checkbox"/> KW4126	Euro american standard 2 P+E 16 A 127/250 V~ universal duplex socket - Ø 5 mm shielded tulip contacts - 2 modules	<input type="checkbox"/> KW52	Cover suitable for all the items over described
<input checked="" type="checkbox"/> KG4126		<input type="checkbox"/> KG52	
<input type="checkbox"/> KM4126		<input type="checkbox"/> KM52	
<input type="checkbox"/> KW4129	American standard 2 P+E 15 A 127/250 V~ socket - shielded tulip contacts - 2 modules	<input type="checkbox"/> KM51	
<input checked="" type="checkbox"/> KG4129		<input type="checkbox"/> KM52	
<input type="checkbox"/> KM4129		<input type="checkbox"/> KM52	
<input type="checkbox"/> KW4185	Euro american standard 2 P+E 16 A 127/250 V~ universal duplex socket - shielded tulip contacts - 3 modules	<input type="checkbox"/> KM51	
<input checked="" type="checkbox"/> KG4185		<input type="checkbox"/> KM52	
<input type="checkbox"/> KM4185		<input type="checkbox"/> KM52	
<input type="checkbox"/> KW4188	American standard 2 P+E 15 A 127/250 V~ universal duplex socket - shielded tulip contacts - 3 modules	<input type="checkbox"/> KM51	
<input checked="" type="checkbox"/> KG4188		<input type="checkbox"/> KM52	
<input type="checkbox"/> KM4188		<input type="checkbox"/> KM52	

**White** colour cover

**Black** colour cover

**Sand** colour cover

Neutral item (without cover)


Items in red colour: New products

## Traditional electrical system

### American standard sockets



KW4188GFG6



KW52

### Multistandard socket Israeli standard sockets



K4139



KM59



KW4183



KG04

Devices to be completed with appropriate cover as indicated below

Item	American standard sockets
<input type="checkbox"/> KW4188GFG6	American standard 2 P+E 15 A 127 V~ GFCI
<input checked="" type="checkbox"/> KG4188GFG6	socket - support frame included - 3 modules
<input type="checkbox"/> KM4188GFG6	

### Multistandard socket

OK4139



Multistandard socket  
- 2 modules

### Israeli standard sockets

KW4183  
 KG4183  
 KM4183




2 P+E 10/16 A 250 Va.c. socket  
- 2 modules

### Cover for american standard sockets

#### 3 modules


KW52  
 KG52  
 KM52

 Cover suitable for all the items over described

### Cover for multistandard socket

#### 2 modules

KW59  
 KG59  
 KM59

 Cover suitable for item K4139

### Cover for israeli standard sockets

#### 2 modules

KW04  
 KG04  
 KM04



Cover suitable for all the items KW4183, KG4183, KM4183

#### 2 modules with hatch

KW04P  
 KG04P  
 KM04P



Cover suitable for all the items KW4183, KG4183, KM4183

#### 3 modules

KW04M3  
 KG04M3  
 KM04M3



Cover suitable for all the items KW4183, KG4183, KM4183

White colour cover

Black colour cover

Sand colour cover

Neutral item (without cover)

Items in red colour: New products


## Traditional electrical system

french/belgian standard sockets, 2 modules,


Cover & Top FLAT socket version




K4142A



KW55F



KM55F



KG55M3F

Devices to be completed with appropriate cover as indicated below

Item	French-Belgium standard sockets	Item	Cover for FLAT socket version
OK4142A	<b>French-Belgium standard sockets</b>  French-Belgian standard socket 2 P+E 16 A 250 V~ - automatic clamps - shielded tulip - 2 modules	<b>2 modules</b> <input type="checkbox"/> KW55F <input checked="" type="checkbox"/> KG55F <input type="checkbox"/> KM55F <input type="checkbox"/> KR55F <input type="checkbox"/> KV55F	Cover for item K4142A (Red and green for special users)
		<input type="checkbox"/> KW55M3F <input checked="" type="checkbox"/> KG55M3F <input type="checkbox"/> KM55M3F	 Cover for item K4142A

**Note:** if replacing only the 3-module cover, order the following codes: KG/KM/KW04M3

### EXAMPLE: FUNCTION & COVER COLOUR CHOICE



**White** colour cover

**Black** colour cover

**Sand** colour cover


**Neutral item (without cover)**

Items in red colour: New products



## Traditional electrical system

french/belgian standard sockets, 2 modules,

Cover & Top STANDARD socket version



Devices to be completed with appropriate cover as indicated below

Item	French-Belgium standard sockets	Item	Cover for STANDARD socket version
OK4142A	<b>French-Belgium standard socket</b> 2 P+E 16 A 250 V~ - automatic clamps - shielded tulip - 2 modules	<b>2 modules</b> <input type="checkbox"/> KW55 <input checked="" type="checkbox"/> KG55 <input type="checkbox"/> KM55 <input type="checkbox"/> KR55 <input type="checkbox"/> KV55	Cover for item K4142A (Red and green for special users)
	 + 	<b>2 modules with hatch</b> <input type="checkbox"/> KW55P <input checked="" type="checkbox"/> KG55P <input type="checkbox"/> KM55P	 +  Cover for item K4142A

**Note:** if replacing only the cover with door, order the following codes: KG/KM/KW04P

### EXAMPLE: FUNCTION & COVER COLOUR CHOICE



## Traditional electrical system

### USB and wireless chargers



K4285C1



K4285C2



K4286C1



K4286C2



K4287C2



KW4286CW2



KW10C



KM10C



KG12C

Devices to be completed with appropriate cover as indicated below

#### Item

#### USB charger

OK4285C1



5 Vdc type A USB charger only for charging electronic devices up to 1,500 mA  
- 110-230 V 50-60 Hz DIRECT power supply  
- 1 module

OK4285C2



5 Vdc type A USB charger for quick charge of one single electronic device up to 3,000 mA or simultaneous charging of two devices up to 1,500 mA  
- 110-230 V 50-60 Hz DIRECT power supply  
- 2 modules

OK4286C1



5 Vdc type C USB charger only for charging electronic devices up to 1,500 mA  
- 110-230 V 50-60 Hz DIRECT power supply  
- 1 module

OK4286C2



5 Vdc type C USB charger for quick charge of one single electronic device up to 3,000 mA or simultaneous charging of two devices up to 1,500 mA  
- 110-230 V 50-60 Hz DIRECT power supply  
- 2 modules

OK4287C2



5 Vdc type A and C USB charger for quick charge of single electronic devices up to 3,000 mA or simultaneous charging of two devices up to 1,500 mA  
- 110-230 V 50-60 Hz DIRECT power supply  
- 2 modules

#### Induction charger

KW4286CW2  
 KG4286CW2  
 KM4286CW2



It allows the quick and wireless charging of smartphones with induction receiver up to 1,000 mA (compliant with WPC Qi standard). The antislip support surface is inclined by 10°. Antitheft lock function. Energy performance >85%. Equipped with a 3.000 mA type-A USB port for the powering of a second device - 12 W. Possibility of simultaneous recharging of two devices, up to 500 mA wirelessly, and up to 1,200 mA through the USB port. Dimension 136.5 x 70 x 56.5 mm. The cover of the selected colour is supplied in the same box as the charger.

#### Item

#### Cover for USB charger

##### 1 module


KW10C  
 KG10C  
 KM10C



Cover for item K4285C1 and K4286C1

##### 2 modules

KW12C  
 KG12C  
 KM12C



Cover for item K4285C2, K4286C2, K4287C2

White colour cover

Black colour cover

Sand colour cover

Neutral item (without cover)

Items in red colour: New products

## Traditional electrical system

### USB charger with socket



KW4141USB



KG4141USB



KM4141USB



KW63



KG63



KM63



KW4142USB



KG4142USB



KM4142USB



KW62



KG62



KM62

Devices to be completed with appropriate cover as indicated below

Item	USB charger with socket outlet
<input type="checkbox"/> KW4141USB	
<input checked="" type="checkbox"/> KG4141USB	German standard electric socket with integrated USB charger. Socket 2 P+E 16 A 250 V~ - protected tulip contacts - side earth contact. 5 Vdc type C USB charger for charging electronic devices up to 1,500 mA. Integrated with a 2-module support, it can be installed instead of an existing socket in a 40 mm deep box. Screw fixing and connection using automatic clamps.
<input type="checkbox"/> KM4141USB	

Item	Cover for USB charger
<input type="checkbox"/> KW63	<b>2 modules</b> 
<input checked="" type="checkbox"/> KG63	Cover for items KW4141USB, KG4141USB, KM4141USB
<input type="checkbox"/> KM63	

Item	Cover for USB charger
<input type="checkbox"/> KW62	<b>2 modules</b> 
<input checked="" type="checkbox"/> KG62	Cover for items KW4142USB, KG4142USB, KM4142USB
<input type="checkbox"/> KM62	



French/Belgian standard flat electric socket with integrated USB charger.  
Socket 2 P+E 16 A 250 V~ - protected tulip contacts.  
When the plug is inserted the socket surface slides inside the casing; it returns to its initial position when the plug is taken out.  
5 Vdc type C USB charger for charging electronic devices up to 1,500 mA.  
Integrated with a 2-module support, it can be installed instead of an existing socket in a 40 mm deep box.  
Screw fixing and connection using automatic clamps.

White colour cover

Black colour cover

Sand colour cover

Neutral item (without cover)


Items in red colour: New products

## Traditional electrical system

### TV sockets



Devices to be completed with appropriate cover as indicated below



Item	TV socket 1 module
OK4202D	Direct coaxial socket for single-user aerial systems, including central remote powered systems and single-user central satellite systems with current and signal transfer for the selection of the channels - shielded connection clamps with captive screws - Diam. 9.5 mm - male connector - 1 module
OK4202P14	Passthrough coaxial socket, -14 dB attenuation, for centralised aerial systems, including central remote powered systems and centralised satellite systems with current and signal transfer for the selection of the channels - shielded connection clamps with captive screws - Diam. 9.5 mm - male connector - 1 module
OK4202P10	Terminal passthrough coaxial socket, 10dB attenuation, for centralised aerial systems, including central remote powered systems and centralised satellite systems with current and signal transfer for the selection of the channels; shielded connection clamps with captive screws - Diam. 9.5 mm - male connector - 75 Ω incorporated impedance final adapter - 1 module
OK4202F	Type F TV coaxial connector - impedance 75 Ω - screw hook - 1 module
OK4214D	Direct demixed coaxial socket for single-user aerial systems, also remote powered and shunting centralised and for single-user / shunting centralised satellite systems with current and signal transfer for the selection of the channels; Ø 9.5 mm male TV connector - type F SAT connector - 1 module

Item	TV socket 2 modules
OK4211M2C	TV-RD socket for cable operator - Double coaxial shunted socket for TV and FM-LMC reception - Ø 9.5mm - Belgium (Telenet operator) - 2 modules
OK4217M2D	Star demixed TV-SAT sockets for DVB-T, cablecast and satellite installation UHD TV, 4GLTE compatible. For distribution of TV & Radio signals. Recommended coaxial cable: 17 VATC - Meet EN 50083 and EN 50083-2 European directive. - TV male connector (Ø9.5 mm) - SAT F type connector - TV: 5-68/120-862 MHz; R: 87.5 - 108 MHz; - SAT: 950-2400 MHz - attenuation 1.5 dB - 2 modules
OK4217MP14	Passthrough demixed TV-SAT sockets for DVB-T, cablecast and satellite installation UHD TV, 4GLTE compatible. For distribution of TV & Radio signals. Meet EN 50083 and EN 50083-2 European directive - TV male connector (Ø9.5 mm) - SAT F type connector - TV: 5-68/120-862 MHz; R: 87.5 - 108 MHz; - SAT: 950-2400 MHz - attenuation 1.5 dB - 2 modules
OK4217M2P10	Terminal demixed TV-SAT sockets for DVB-T, cablecast and satellite installation UHD TV, 4GLTE compatible. For distribution of TV & Radio signals. Meet EN 50083 and EN 50083-2 European directive - TV male connector (Ø9.5 mm) - SAT F type connector - TV: 5-68/120-862 MHz; R: 87.5 - 108 MHz; - SAT: 950-2400 MHz - attenuation 10 dB - 2 modules
OK4210M2D	Star demixed TV-R-SAT sockets for DVB-T, cablecast and satellite installation UHD TV, 4GLTE compatible. For distribution of TV & Radio signals. Recommended coaxial cable: 17 VATC - Meet EN 50083 and EN 50083-2 European directive. - TV male connector (Ø 9.5 mm) - R female connector (Ø9.5 mm) - SAT F type connector - TV: 5-68/120-862 MHz; R: 87.5 - 108 MHz; - SAT: 950-2400 MHz - attenuation 1.5 dB - 2 modules

Item	Cover for TV socket 1 module
<b>1 module</b>	
<input type="checkbox"/> KW08	
<input checked="" type="checkbox"/> KG08	
<input type="checkbox"/> KM08	
<input type="checkbox"/> KW09	
<input checked="" type="checkbox"/> KG09	
<input type="checkbox"/> KM09	
<input type="checkbox"/> KW08M2	
<input checked="" type="checkbox"/> KG08M2	
<input type="checkbox"/> KM08M2	
<b>2 modules</b>	
<input type="checkbox"/> KW08M2	
<input checked="" type="checkbox"/> KG08M2	
<input type="checkbox"/> KM08M2	

Item	Cover for TV socket 2 modules
<b>2 modules</b>	
<input type="checkbox"/> KW25M2	
<input checked="" type="checkbox"/> KG25M2	
<input type="checkbox"/> KM25M2	
<input type="checkbox"/> KW26M2	
<input checked="" type="checkbox"/> KG26M2	
<input type="checkbox"/> KM26M2	
<b>Cover for TV-SAT sockets - no brand BTicino</b>	
<b>2 modules</b>	
<input type="checkbox"/> KW4212	
<input checked="" type="checkbox"/> KG4212	
<input type="checkbox"/> KM4212	

White colour cover

Black colour cover

Sand colour cover

Cover for TV-SAT sockets

Items in red colour: New products

Neutral item (without cover)

## Traditional electrical system

RJ connectors for data, telephony and for optical fiber



Devices to be completed with appropriate cover as indicated below

Item	RJ45 connectors		Item	Cover for RJ45, RJ11 connectors and Keystons adapters	
	Connectors for data/telephony transmission These connectors can be used for 4-pair signal transmission systems - 1 module			<b>1 module</b>	
<input type="checkbox"/> KW4279C5E <input checked="" type="checkbox"/> KG4279C5E <input type="checkbox"/> KM4279C5E	Category 5E UTP	Type of connection TOOLLESS IDC		<input type="checkbox"/> KW07 <input checked="" type="checkbox"/> KG07 <input type="checkbox"/> KM07	Cover for all the RJ45 and RJ11 connectors
<input type="checkbox"/> KW4279C6 <input checked="" type="checkbox"/> KG4279C6 <input type="checkbox"/> KM4279C6	6 UTP	TOOLLESS IDC		<input type="checkbox"/> KW07M2 <input checked="" type="checkbox"/> KG07M2 <input type="checkbox"/> KM07M2	<b>2 modules</b> Cover for all the RJ45 and RJ11 connectors
<input type="checkbox"/> KW4279C6S <input checked="" type="checkbox"/> KG4279C6S <input type="checkbox"/> KM4279C6S	6 STP	TOOLLESS IDC		<input type="checkbox"/> KW20 <input checked="" type="checkbox"/> KG20 <input type="checkbox"/> KM20	<b>Cover for telephone socket standard BS</b> <b>2 modules</b> Cover for item K4238
<input type="checkbox"/> KW4279C6A <input checked="" type="checkbox"/> KG4279C6A <input type="checkbox"/> KM4279C6A	6A UTP	TOOLLESS IDC		<input type="checkbox"/> KW13M2 <input checked="" type="checkbox"/> KG13M2 <input type="checkbox"/> KM13M2	<b>Cover for optical fiber connector</b> <b>2 modules</b> Cover for item K4268SCA
<input type="checkbox"/> KW4279C6AS <input checked="" type="checkbox"/> KG4279C6AS <input type="checkbox"/> KM4279C6AS	6A STP	TOOLLESS IDC			
<b>RJ11 connectors</b>					
	These connectors are designed to meet the needs linked with telephonic interconnections - 1 module				
<input type="checkbox"/> KW4258RJ11 <input checked="" type="checkbox"/> KG4258RJ11 <input type="checkbox"/> KM4258RJ11	Category RJ11	Type of connection K10			
OK4238	<b>Telephone socket standard BS</b> Telephone socket standard BS - 1 module				
OK4268SCA	<b>Connector for optical fiber</b> Coupling connector for optical fiber - SC cable socket - duplex - 2 modules				
<b>KEYSTONE</b>					
<input type="checkbox"/> KW07K <input checked="" type="checkbox"/> KG07K <input type="checkbox"/> KM07K	Keystone connectors adapter - 1 module				

**White** colour cover

**Black** colour cover

**Sand** colour cover

**Neutral item (without cover)**

Items in red colour: New products

## Traditional electrical system

### audio video connectors



Devices to be completed with appropriate cover as indicated below

Item	Audio Connector	Item	Cover for audio and A/V connectors
<input type="checkbox"/> KW4269R	Double RCA module - 1 module	<input type="checkbox"/> KW07	Cover for item KW4269R, KG4269R, KM4269R, KW4294, KG4294 and KM4294
<input checked="" type="checkbox"/> KG4269R		<input type="checkbox"/> KG07	
<input type="checkbox"/> KM4269R		<input type="checkbox"/> KM07	
<input type="checkbox"/> KW4294	Home cinema speaker connector - 1 module	<input type="checkbox"/> KW14	Cover for item K4284P
<input checked="" type="checkbox"/> KG4294		<input type="checkbox"/> KG14	
<input type="checkbox"/> KM4294		<input type="checkbox"/> KM14	
 	<b>A/V connector</b>	 	 
<input type="radio"/> K4284P	Pre-connected HDMI 1.4 connector - 1 module	<input type="checkbox"/> KW10P	Cover for item K4285P
<input type="radio"/> K4285P	Pre-connected type A USB connector - 1 module	<input type="checkbox"/> KG10P	
		<input type="checkbox"/> KM10P	
		 	<b>2 modules</b>
		<input type="checkbox"/> KW07M2	Cover for item KW4269R, KG4269R, KM4269R, KW4294, KG4294 and KM4294
		<input checked="" type="checkbox"/> KG07M2	
		<input type="checkbox"/> KM07M2	

**White** colour cover

**Black** colour cover

**Sand** colour cover

Neutral item (without cover)

Items in red colour: New products

# Traditional electrical system

## luminous and audible notification



K4351V230

K4356V230

K4355V12

K4371



KW15

KW15M2

KG15M2

KG08

KM09

Devices to be completed with appropriate cover as indicated below

Item	Bells and buzzer
OK4351V230	<b>Bells</b> 230 V~ bronze bell - 12 VA - 80 dB - 1 module
OK4351V127	127 V~ bronze bell - 8 VA - 80 dB - 1 module
OK4351V12	12 V~ bronze bell - 8 VA - 80 dB - 1 module
OK4355V12	Electronic bell - 3 different sounds - with front volume adjustment - 12 Va.c.-d.c. power supply - 2 modules
OK4356V230	<b>Buzzer</b> 230 V~ buzzer - 12 VA - 80 dB - 1 module
OK4356V127	127 V~ buzzer - 12 VA - 80 dB - 1 module
OK4356V12	12 V~ buzzer - 12 VA - 80 dB - 1 module

Item	Pilot lamp
OK4371	Lampholder for pilot lamp with transparent diffuser, to be completed with LED item K4743V230 (white) and/or item K4743V230R (red). Two operating mode: - 1 luminous signaling (to be completed with cover KW/KG/KM08) - 2 luminous signaling (to be completed with cover KW/KG/KM09)

Réf.	Cover for bell and buzzer
<input type="checkbox"/> KW15	<b>1 module</b> Cover for item K4351V230, K4351V127, K4351V12, K4356V230, K4356V127 and K4356V12
<input checked="" type="checkbox"/> KG15	
<input type="checkbox"/> KM15	
<input type="checkbox"/> KW15M2	<b>2 modules</b> Cover for item K4355V12
<input checked="" type="checkbox"/> KG15M2	
<input type="checkbox"/> KM15M2	
<input type="checkbox"/> KW08	<b>Cover for pilot lamp</b>
<input checked="" type="checkbox"/> KG08	<b>1 module</b> Cover for item K4371 (one luminous signal)
<input type="checkbox"/> KM08	
<input type="checkbox"/> KW09	
<input checked="" type="checkbox"/> KG09	Cover for item K4371 (two luminous signals)
<input type="checkbox"/> KM09	

**White** colour cover

**Black** colour cover

**Sand** colour cover

Neutral item (without cover)

Items in red colour: New products

## Traditional electrical system lighting



Devices to be completed with appropriate cover as indicated below

Item
<input type="checkbox"/> KW4362
<input checked="" type="checkbox"/> KG4362
<input type="checkbox"/> KM4362

### Reading lamp



It is installed at the bedhead giving directional lighting. It has a flexible arm so that the lighting arm can be directed. The brightness can be dimmed by pressing the integrated ON/OFF control for a long time. It can also be connected to a remote control and, if necessary, the integrated control can be disabled with a 30 sec. press. - LED lamp - 3W consumption - Luminous flux 110 lumen (equivalent to 15 W incandescence) - Life 40,000 hours - 1 module (flush-mounted). Cover supplied with device.

Item
<input type="checkbox"/> OK4380
<input type="checkbox"/> O4380NB
<input type="checkbox"/> OK4381

### Torch and safety LED lamp



Removable and rechargeable torch with automatic switching on device - it lights up automatically when there is a power cut - push&pull pull-out system complete with recharge base - white light LED with high luminous efficiency - ON/OFF switch and SPOT pushbutton to increase the brightness when necessary - interchangeable Ni-MH batteries without "memory" effect - 2 hour life - low consumption in stand-by 0.4 W - 230 V~ power supply - 2 modules



Spare batteries for removable torch



LED safety lamp with automatic operation when there is a power cut. 230 V~ 50/60 Hz - power consumption 2.5 VA (0.1 W) - rechargeable non-replaceable NiMH 3.6 V 140 mAh battery - complete charge in 48 hours - life 2 hours - maximum cable section 1 x 1.5 mm<sup>2</sup> - light intensity 2400 mcd - angle of emission 120° - not pull-out - 1 module

Item
<input type="checkbox"/> OK4382

### Step marker lamp



Step marker lamps with white light LEDs - 127/230 V~ - on-off switch - 0.15-0.5 W - 2 modules

Item
<input type="checkbox"/> KW02
<input checked="" type="checkbox"/> KG02
<input type="checkbox"/> KM02

### Cover for lighting functions

#### 1 module

Cover for item K4381



#### 2 modules

Cover for item K4380



Cover for item K4382



White colour cover

Black colour cover

Sand colour cover

Neutral item (without cover)

Items in red colour: New products

## Traditional electrical system

### functions for hotel room



K4549

K4027H

K4284P

KW4177

KW22

KG22

KW06H

KG06H

KM11H

Devices to be completed with appropriate cover as indicated below

Item	Key card switches	Item	Cover for functions for hotel
OK4549	 <p>Key card switch for the power supply inside the hotel room - slot light with built-in lamp - 30 second switch-off delay - power supply 230 V~. The completion of the light point requires two "half-module blanking modules" (item K4949) at the sides of the badge holder. To be installed with supports and cover plates with minimum size of 3 modules</p>	<input type="checkbox"/> KW06H <input checked="" type="checkbox"/> KG06H <input type="checkbox"/> KM06H	<b>1 module</b>  Cover for item K4027H and K4027V127H
OK4548	 <p>Key card switch for the power supply inside the hotel room - slot light with built-in lamp - 30 second switch-off delay - power supply 230 V~ - with RFID technology recognition. The completion of the light point requires two "half-module blanking modules" (item K4949) at the sides of the badge holder. To be installed with supports and cover plates with minimum size of 3 modules</p>	<input type="checkbox"/> KW11H <input checked="" type="checkbox"/> KG11H <input type="checkbox"/> KM11H	 Cover for item K4373
OK4027H	 <p>1P 10 AX, 250 V~ changeover switch, double-key 1-0-2 for Hotel, LIT - 1 module (The LED is replaceable with item K4743V230RG)</p>	<input type="checkbox"/> KW22M2 <input checked="" type="checkbox"/> KG22M2 <input type="checkbox"/> KM22M2	<b>2 modules</b>  Cover for item K4549 et K4548
OK4027V127H	 <p>As above, 127 V~ (The LED is replaceable with Item K4373V127RG)</p>	<input type="checkbox"/> KW22 <input checked="" type="checkbox"/> KG22 <input type="checkbox"/> KM22	<b>3 modules</b>  Cover for item K4549 et K4548
OK4373	 <p>Lampholder with two built-in LEDs, green and red. Can be used as out of room visual signal with double notification: do not disturb and make up the room - The LEDs cannot be replaced - 127/ 230 V~ power supply - 1 module</p>		
Item	Off-door controls	Item	
OK4177	 <p>Shaver socket with insulation transformer            - input voltage 230 V~ 50/60 Hz            - output voltage 115/230 V~ 20 VA            The cover of the selected colour is supplied in the same box as the shaver socket            - 3 modules</p>	<input type="checkbox"/> KW4177 <input checked="" type="checkbox"/> KG4177 <input type="checkbox"/> KM4177	

#### Shaver sockets

KW4177  
 KG4177  
 KM4177


 Shaver socket with insulation transformer  
 - input voltage 230 V~ 50/60 Hz  
 - output voltage 115/230 V~ 20 VA  
 The cover of the selected colour is supplied in the same box as the shaver socket  
 - 3 modules

**White** colour cover

**Black** colour cover

**Sand** colour cover

**Neutral item (without cover)**

Items in red colour: New products

## Traditional electrical system

### LED and blanking modules




Devices to be completed with appropriate cover as indicated below


Item	LED for control and socket lighting	Item	Blanking modules
K4743V230T	LED for backlighting of the following "basic control devices": K4001, K4001A, K4003, K4003A, K4005, K4005A, K4001M2A, K4003M2A, K4005M2A, KW4002, KG4002, KM4002 et K4034 white LED - 230 V~ - high luminosity for daytime load notification	K4950	Blanking module - 1 module 
K4743V127T	white LED - 127 V~ - high luminosity for daytime load notification	K4953	Blanking module with output Ø 9 mm - 1 module 
K4743V230R	red LED - 230 V~ - high luminosity for daytime load notification		
LN4743/230T	white LED - 230 V~ - night signal	K4949	<b>Installation accessory</b> 1/2 module blanking module - it does not require the cover 
LN4743/12T	white LED - 12/24 V~ - night signal		
H4743/230B	blue LED - 230 V~ - night signal		
H4743/12B	blue LED - 12/24 V~ - night signal		
H4743V230RG	Replacement LED for changeover switch (hotel control) Red/green LED - 230 V~ for item K4027H	<b>Cover for Blanking modules</b>	<b>1 module</b>
H4743V127RG	Red/green LED - 127 V~ for item K4027V127H	<input type="checkbox"/> KW00 <input checked="" type="checkbox"/> KG00 <input type="checkbox"/> KM00	
		<input type="checkbox"/> KW08 <input checked="" type="checkbox"/> KG08 <input type="checkbox"/> KM08	
		<input type="checkbox"/> KW00M2 <input checked="" type="checkbox"/> KG00M2 <input type="checkbox"/> KM00M2	<b>2 modules</b> 

### EXAMPLES OF LED CONNECTION ON A SWITCH

Function: locating



Function: load status LED



Control backlighting led connection

Note for the connection of 230 V.a.c. LEDs for the backlighting of control devices: when LEDs are fitted to help locate the control itself, it must be taken into account that energy saving and fluorescent lamps do not allow in series connection of the LED on the load. It is therefore necessary to also take a neutral conductor near the control, so that the LED may be connected directly between phase and neutral, and will always be on.

White colour cover

Black colour cover


Sand colour cover

Neutral item (without cover)

Items in red colour: New products

## Living Now


support frames and IP44 housing



Item	Supports
K4702	2-module support frame supplied with protective shell
K4703	3-module support frame supplied with protective shell
K4704	4-module support frame supplied with protective shell
K4706	6-module support frame supplied with protective shell
500/00	Pair of 35 mm screws for the fastening of the supports to boxes installed below the plaster work.
K8102	Support for the installation of the electrified frame item KW8102P1, KG8102P1, KM8102P1 in 2 module box

Item	IP44 housing
26603	IP44 protection cover (guaranteed when closed). Ideal for installation where an IP44 protection degree is required. Fully compatible with all ranges, both BTicino and other brands. It is made with high-quality material which guarantees long-term sealing against all weather conditions. It can be installed on Italian standard 3-module flush mounted box

Item	Various accessories
503CG	Protective cover for flush mounted box item 503E - to be used during finishing masonry works
503EV	Internal resin separator - for box item 503E - for the separation of data and power circuits
503EC	Finishing cover for flush mounted box item 503E - to be used when the box is used as a junction box - can be painted
504EC	Cover as above, for boxes item 504E
506EC	Cover as above, for boxes item 506E
503DE	Internal resin separator - for box item 504E
503ED	Coupling for boxes items 502E, 503E, 504E (horizontal and vertical) and for box 506L (only vertical). It cannot be used with the box extension



## Traditional electrical system

lightable cover with symbols, for items:

**K4001, K4003, K4004, K4004L, K4004LB, K4005, K4034**

COVER	Item	Cover for the command of heating, ventilation, boiler
	KW01PN	Cover 1 module. Heating comand
	KG01PN	White
	KM01PN	Black
	KW01RN	Cover 1 module. Ventilation comand
	KG01RN	White
	KM01RN	Black
	KW01SN	Cover 1 module. Boiler comand
	KG01SN	White
	KM01SN	Black
	KW01M2PN	Cover 2 module. Heating comand
	KG01M2PN	White
	KM01M2PN	Black
	KW01M2RN	Cover 2 module. Ventilation comand
	KG01M2RN	White
	KM01M2RN	Black
	KW01M2SN	Cover 2 module. Boiler comand
	KG01M2SN	White
	KM01M2SN	Black

Living Now WITH **Netatmo**



**SMART ELECTRICAL SYSTEM**



Devices to be completed with appropriate cover as indicated below

Item	Connected devices for light	Connected devices for shutters
OK4001C	<p>Connected one-way switch. It controls the lights locally or remotely. It can be installed like a traditional two-way switch and is compatible with all loads with max power 250 W. It has a blue LED, which can be configured using the Home + Control App for the localisation and load status functions. It can be associated to one or more wireless controls. Caution: neutral connection is necessary. Power supply 110-230 V~ - 1 module</p>	<p>Connected rolling shutter switch - It allows the control of a shutter locally or remotely. Compatible with all standard rolling shutter motors (with a mechanical or electromechanical stop and max power 500 VA) controlled by a wired shutter switch (switching of the same motor power supply). Not compatible with motors for radio-controlled or pulse-controlled roller shutters. It can be associated with one or more wireless commands. Caution: Must be connected to the neutral. Power supply 110-230 V~ - 1 module</p>
OK4003C	<p>Connected 2ways switch. It allows to control lights locally or remotely. The connected 2ways switch has the same installation and usability of a traditional 2ways switch and it is compatible with all loads with max power 250 W. It is equipped with a blue LED light used always on for localization modality or on, when the light is on for the load status modality. It can be associated with "wireless light switches". Caution: Must be connected to the neutral. Power supply 110-230 V~ - 1 module</p>	<p>Connected micromodule for shutters. Associated to one or more shutter wireless controls, it controls a shutter locally or remotely. Compatible with all standard shutter motors (with mechanical or electronic limit switch and maximum power 500 VA), controlled by a wired shutter changeover switch (changeover with the same power supply as the motor). Not compatible with radio controlled or pulse controlled shutter motors. It can be installed in the existing shutter box with no need of masonry works. Power supply 110-230 V~</p>
O3584C	<p>Connected lighting micromodule. It allows to control lights locally or remotely. It is compatible with all loads with max power 300 W. It can be connected to one or more traditional push-button or associated with "wireless light switches". It is installed as a traditional relay in the box (behind the button) or in derivation boxes. Caution: Must be connected to the neutral. Power supply 110-230 V~</p>	
OFC80RC	<p>DIN switchboard light device for loads with absorption In= 16 A. Equipped with a meter measuring the current absorbed by the load and contacts for control with up to 10 pushbuttons. 1 DIN module. Power supply 110-230 V~</p>	
OK4411C	<p>Dimmer/switch. It allows to control lights locally or remotely, with the dimmer functionality that can be activated from APP Home+Control. It has the same installation and usability of a traditional switch and it is compatible with all loads (LED, halogen) with max power 150 W at 230 V (or 75 W at 110 V). It is equipped with a blue LED light used for localization modality or load status modality, configurable by APP. It can be connected to one or more traditional push-button or associated with "wireless light switches". Caution: Must be connected to the neutral. Power supply 110-230 V~ - 1 module</p>	
<b>Cover</b>		
<b>1 module</b>		
<input type="checkbox"/> KW01 <input checked="" type="checkbox"/> KG01 <input type="checkbox"/> KM01		
<input type="checkbox"/> KW33 <input checked="" type="checkbox"/> KG33 <input type="checkbox"/> KM33		
<input type="checkbox"/> KW32 <input checked="" type="checkbox"/> KG32 <input type="checkbox"/> KM32		
<b>2 modules</b>		
<input type="checkbox"/> KW01M2 <input checked="" type="checkbox"/> KG01M2 <input type="checkbox"/> KM01M2		
<input type="checkbox"/> KW32M2 <input checked="" type="checkbox"/> KG32M2 <input type="checkbox"/> KM32M2		



**App HOME + CONTROL** for  
management of connected devices



**Note:** for the use of the connected devices, the gateway, item **K4500C**, item **K4510C** or item **FC80GT**, must be installed as part of the system.

**White** colour cover

**Black** colour cover

**Sand** colour cover


Neutral item (without cover)

Items in red colour: New products



# Living Now with Netatmo smart electrical system - MODULAR VERSION

wireless controls for light and shutter



K4003CWI

K4003CW



K4003DCW



3585C



KW01

KM32

KW36M2



KW43M2

Devices to be completed with appropriate cover as indicated below

Item	Wireless controls for light	Item	Motion sensor wireless
○ K4003CWI	<p></p> <p>Wireless light switch. It allows the ON / OFF and dimming control of one or more connected devices for the lighting control. It can be installed in any flush-mounted box without any wiring. The battery can be replaced without removing it from the supporting frame. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 1 module</p>	○ 3585C	<p></p> <p>It controls one or more devices connected for light control. Infrared detection with angle of 140°. Distance of the adjustable sensor from 2 to 8 m. Switch off delay with 1 to 30 min adjustable delay time and 1 to 1000 lux brightness threshold. Test possible with a 5 sec. delay. Recommended assembly height: 2.5 m. Optimum distance between 2 detectors: 6 m. For indoor and outdoor use (IP44). Supplied with 2 1.5V AA batteries for power supply.</p>
○ K4003CW	<p></p> <p>Wireless light switch. It allows the ON / OFF and dimming control of one or more connected devices for the lighting control. Surface installation with repositionable stickers (supplied) or onto a flush mounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules</p>		
○ K4003DCW	<p></p> <p>Wireless light switch. It is equipped with two buttons to control two different connected devices for lights. Each single button can be associated with one or more devices. Surface installation with repositionable stickers (supplied) or onto a flush mounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules</p>		
○ 3577C	<p></p> <p>Wireless module for mechanical switch. It allows to change a two-way switch or a traditional pushbutton into a wireless light control for ON/OFF control of one or more devices connected for light control. The small size allows the installation in the flush mounted box. CR2032 type 3V power battery with 8 year expected life supplied (as standard).</p>		
	<b>Wireless controls for shutter</b>		<b>Cover</b>
○ K4027CWI	<p></p> <p>Rolling shutter wireless switch - It allows the control of one or more connected rolling shutter switches. It can be installed in any flush-mounted box without any wiring. The battery can be replaced without removing it from the supporting frame. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 1 module</p>	<p><input type="checkbox"/> KW01</p> <p><input checked="" type="checkbox"/> KG01</p> <p><input type="checkbox"/> KM01</p> <p><input type="checkbox"/> KW33</p> <p><input checked="" type="checkbox"/> KG33</p> <p><input type="checkbox"/> KM33</p> <p><input type="checkbox"/> KW32</p> <p><input checked="" type="checkbox"/> KG32</p> <p><input type="checkbox"/> KM32</p>	<p>Cover for item K4003CWI</p> <p>Cover for item K4003CW</p> <p>Cover for item K4027CWI</p>
○ K4027CW	<p></p> <p>Rolling shutter wireless switch - It allows the control of one or more connected rolling shutter switches. Surface installation with repositionable stickers (supplied) or onto a flush mounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules</p>	<p><input type="checkbox"/> KW42M2</p> <p><input checked="" type="checkbox"/> KG42M2</p> <p><input type="checkbox"/> KM42M2</p> <p><input type="checkbox"/> KW36M2</p> <p><input checked="" type="checkbox"/> KG36M2</p> <p><input type="checkbox"/> KM36M2</p> <p><input type="checkbox"/> KW43M2</p> <p><input checked="" type="checkbox"/> KG43M2</p> <p><input type="checkbox"/> KM43M2</p>	<p>Cover for item K4003DCW</p> <p>Cover for item K4027CW</p>

White colour cover

Black colour cover

Sand colour cover

○ Neutral item (without cover)

Items in red colour: New products



Devices to be completed with appropriate cover as indicated below


Item	Wireless Home/Away scenario controls	Item	Cover
OK4570CWI	<p>Home / Away wireless switch. It is equipped with 2 buttons for activating Home / Away scenarios. Scenarios can be customized by the Home + Control app. It can be installed in any flush-mounted box without any wiring. The battery can be replaced without removing it from the supporting frame. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 1 module</p>	<input type="checkbox"/> KW40 <input checked="" type="checkbox"/> KG40 <input type="checkbox"/> KM40	<b>1 module</b>       
OK4570CW	<p>Home / Away wireless switch. It is equipped with 2 buttons for activating Home / Away scenarios. Scenarios can be customized by the Home + Control app. Surface installation with repositionable stickers (supplied) or onto a flush mounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules</p>	<input type="checkbox"/> KW40M2 <input checked="" type="checkbox"/> KG40M2 <input type="checkbox"/> KM40M2	<b>2 modules</b>       
OK4574CWI	<p>Wireless Wake Up / Sleep scenario controls</p> <p>It is equipped with 2 buttons for activating Wake Up / Sleep scenarios. Scenarios can be customized by the Home + Control app. It can be installed in any flush-mounted box without any wiring. The battery can be replaced without removing it from the supporting frame. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 1 module</p>	<input type="checkbox"/> KW41 <input checked="" type="checkbox"/> KG41 <input type="checkbox"/> KM41	     
OK4574CW	<p>Wireless Wake Up / Sleep scenario controls</p> <p>It is equipped with 2 buttons for activating Wake Up / Sleep scenarios. Scenarios can be customized by the Home + Control app. Surface installation with repositionable stickers (supplied) or onto a flush mounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules</p>	<input type="checkbox"/> KW41M2 <input checked="" type="checkbox"/> KG41M2 <input type="checkbox"/> KM41M2	      
OK4575CW	<p>Wireless 4 scenarios control</p> <p>It's equipped with 4 buttons for activating of scenarios 1,2,3 and 4. Scenarios can be customized by the Home+ Control app. Surface installation with repositionable stickers (supplied) or onto a flushmounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules.</p>	<input type="checkbox"/> KW37 <input checked="" type="checkbox"/> KG37 <input type="checkbox"/> KM37	   

# Living Now with Netatmo smart electrical system - MODULAR VERSION

wireless controls and controls for energy management and gateway



Devices to be completed with appropriate cover as indicated below

Item	Connected module for energy management	Item	Gateway
OK4531C	 <p>Connected socket module - wiring to a power outlet, allows to remotely control appliances and check the consumption (instantaneous, daily, monthly). It is also possible to receive notifications in case of anomalous consumption. The connected socket module is compatible with any device electric and large appliances up to 16 A 3680 W max. (protected against overloads). It is equipped with a LED light lit in blue when it is on. This option can be enabled or disabled in the "Home+Control" app. It can be associated with "wireless light switches". Power supply 110-230 V~ - 1 module</p>	OK4500C	 <p>Gateway. This pack enables to create a connected installation in the home. It can be used to control lighting, roller shutters and electrical equipment plugged into connected sockets:</p> <ul style="list-style-type: none"> <li>- using your smartphone and the Home + Control app</li> <li>- using voice assistants</li> <li>- from the general control at the entrance to your home</li> </ul> <p>Supplied with the Home/Away wireless master switch required for the association procedure of all connected devices.</p> <p>Power supply 110-230 V~ - 2 modules</p>
4141PC	 <p>Connected Presa plug&amp;play socket. Directly connected to an existing socket, it allows remote control of all the connected electrical appliances. It also monitors the instantaneous, daily and monthly consumption. Compatible with all the devices with power up to 16 A 3680 W (with overload protection). It can be associated to wireless light controls. Power supply 110-230 V~</p>	K4510C	 <p>Gateway as above. Supplied with the flush-mounted Home/Away wireless master switch 1 module required for the association procedure of all connected devices.</p> <p>Power supply 110-230 VA - 2 modules</p>
4142PC	 <p>As above French/belgian standard socket.</p>	FC80GT	 <p>Gateway as above for DIN switchboard. Supplied without wireless In&amp;Out master scenario control item K4570CW.</p> <p>- 2.5 DIN modules.</p>
FC80CC	 <p>Connected contactor for single-phase and/or three-phase loads with maximum absorption <math>I_{n}=20</math> A. With meter for the measurement of the current absorbed by the load. Power supply 110-230 V~ - 1 DIN module</p>	<p><b>Cover for item K4531C</b></p> <p><b>1 module</b></p> <p><input type="checkbox"/> KW31 <input checked="" type="checkbox"/> KG31 <input type="checkbox"/> KM31</p>	
F20T60A	 <p>Connected DIN meter. It allows to measure the energy consumption of the house electric installation (instantaneous, daily, monthly). It is also possible to receive notifications in case of exceeded the maximum power provided by your contract to avoid possible black-out. A toroid is provided to read the current. Power supply 110-230 V~ - 1 DIN module</p>	<p><b>Cover required for the gateway</b></p> <p><b>2 modules</b></p> <p><input type="checkbox"/> KW30M2 <input checked="" type="checkbox"/> KG30M2 <input type="checkbox"/> KM30M2</p>	
FC80GCS	 <p>Connected DIN load management module for the monitoring of the consumptions of the whole electric system, the powering or disconnection of the loads, and the setting of scenarios with priority or non-priority loads. When the maximum intended power is reached, the non-priority loads are temporarily disconnected to avoid black-outs. A toroid for the current reading is provided. Power supply 110-230 V~ - 1 DIN module</p>	<p><b>Cover for the gateway scenario control</b></p> <p><b>1 module</b></p> <p><input type="checkbox"/> KW40 <input checked="" type="checkbox"/> KG40 <input type="checkbox"/> KM40</p>	
		<p><b>2 modules</b></p> <p><input type="checkbox"/> KW40M2 <input checked="" type="checkbox"/> KG40M2 <input type="checkbox"/> KM40M2</p>	



Devices to be completed with appropriate cover as indicated below

Item	Connected devices for light	Connected devices for shutters
○ 3584C	<p>Connected lighting micromodule. It allows to control lights locally or remotely. It is compatible with all loads with max power 300 W. It can be connected to one or more traditional push-button or associated with "wireless light switches". It is installed as a traditional relay in the box (behind the button) or in derivation boxes. Caution: Must be connected to the neutral. Power supply 110-230 V~</p>	<p>Connected shutter control for the local or remote control of a shutter. Compatible with all standard shutter motors (with mechanical or electronic limit switch and maximum power 500 VA), controlled by a wired shutter changeover switch (changeover with the same power supply as the motor). Not compatible with radio controlled or pulse controlled shutter motors. It can be associated to one or more wireless controls. Power supply 110-230 V~</p>
○ FC80RC	<p>DIN switchboard light device for loads with absorption In= 16 A. Equipped with a meter measuring the current absorbed by the load and contacts for control with up to 10 pushbuttons.. Power supply 110-230 V~</p>	<p>- 1 DIN module</p>
○ K4411CM2	<p>Dimmer/switch without neutral. It allows to control lights locally or remotely, with the dimmer functionality that can be activated from APP Home+Control. It has the same installation and usability of a traditional switch and it is compatible with all loads (LED, halogen) with power 5-300 W at 230 V. It is equipped with a blue LED light used for localization modality or load status modality, configurable by APP. It can be connected associated with "wireless light switches". It doesn't require connection to the neutral, it comes with an active compensator. Power supply 110-230 V~</p>	<p>- 2 modules</p>
		<p>Connected micromodule for shutters. Associated to one or more shutter wireless controls, it controls a shutter locally or remotely. Compatible with all standard shutter motors (with mechanical or electronic limit switch and maximum power 500 VA), controlled by a wired shutter changeover switch (changeover with the same power supply as the motor). Not compatible with radio controlled or pulse controlled shutter motors. It can be installed in the existing shutter box with no need of masonry works. Power supply 110-230 V~</p>
		<p><b>Cover</b></p> <p><b>2 modules</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> KW33M2</li> <li><input checked="" type="checkbox"/> KG33M2</li> <li><input type="checkbox"/> KM33M2</li> </ul> <ul style="list-style-type: none"> <li><input type="checkbox"/> KW43M2</li> <li><input checked="" type="checkbox"/> KG43M2</li> <li><input type="checkbox"/> KM43M2</li> </ul>
		<p>Cover for item K4411CM2</p>
		<p>Cover for item K4027CM2</p>



**App HOME + CONTROL** for management of connected devices



**Note:** for the use of the connected devices, the gateway, item **K4500C**, item **K4510C** or item **FC80GT**, must be installed as part of the system.

**White** colour cover

**Black** colour cover

**Sand** colour cover

**Neutral item (without cover)**

Items in red colour: New products




# Living Now with Netatmo smart electrical system - EUROPEAN VERSION

wireless controls for light and shutter



K4003CW



K4003DCW



3585C



KW36M2



KW32M2

Devices to be completed with appropriate cover as indicated below

Item	Wireless controls for light	Item	Motion sensor wireless
OK4003CW	<p><b>Wireless controls for light</b></p> <p>Wireless light switch. It allows the control of one or more connected devices for the lighting control. Surface installation with repositionable stickers (supplied) or onto a flush mounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules</p>	3585C	<p><b>Motion sensor wireless</b></p> <p>It controls one or more devices connected for light control. Infrared detection with angle of 140°. Distance of the adjustable sensor from 2 to 8 m. Switch off delay with 1 to 30 min adjustable delay time and 1 to 1000 lux brightness threshold. Test possible with a 5 sec. delay. Recommended assembly height: 2.5 m. Optimum distance between 2 detectors: 6 m. For indoor and outdoor use (IP44). Supplied with 2 1.5V AA batteries for power supply.</p>
OK4003DCW	<p>Wireless light switch. It is equipped with two buttons to control two different connected devices for lights. Each single button can be associated with one or more devices. Surface installation with repositionable stickers (supplied) or onto a flush mounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules</p>		
OK4027CW	<p><b>Wireless controls for shutter</b></p> <p>Rolling shutter wireless switch - It allows the control of one or more connected rolling shutter switches. Surface installation with repositionable stickers (supplied) or onto a flush mounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules</p>	<p><b>Cover</b></p> <p><b>2 modules</b></p> <p><input type="checkbox"/> KW42M2  <input checked="" type="checkbox"/> KG42M2  <input type="checkbox"/> KM42M2</p> <p><input type="checkbox"/> KW36M2  <input checked="" type="checkbox"/> KG36M2  <input type="checkbox"/> KM36M2</p> <p><input type="checkbox"/> KW43M2  <input checked="" type="checkbox"/> KG43M2  <input type="checkbox"/> KM43M2</p>	 Cover for item K4003CW  Cover for item K4003DCW  Cover for item K4027CW


**White** colour cover

**Black** colour cover

**Sand** colour cover

**Neutral item (without cover)**

Items in red colour: New products



OK4570CW



K4574CW



KG40M2



KM40M2



KW41M2



KG37M2

Devices to be completed with appropriate cover as indicated below

Item	Wireless Home/Away scenario controls	Item	Cover
OK4570CW	<p>Home / Away wireless switch. It is equipped with 2 buttons for activating Home / Away scenarios. Scenarios can be customized by the Home + Control app. Surface installation with repositionable stickers (supplied) or onto a flush mounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules</p>	<input type="checkbox"/> KW40M2 <input checked="" type="checkbox"/> KG40M2 <input type="checkbox"/> KM40M2	<b>2 modules</b>  Cover for item K4570CW
OK4574CW	<p>Wireless Wake Up / Sleep scenario controls. It is equipped with 2 buttons for activating Wake Up / Sleep scenarios. Scenarios can be customized by the Home + Control app. Surface installation with repositionable stickers (supplied) or onto a flush mounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules</p>	<input type="checkbox"/> KW41M2 <input checked="" type="checkbox"/> KG41M2 <input type="checkbox"/> KM41M2	 Cover for item K4574CW
OK4575CW	<p>Wireless 4 scenarios control. It's equipped with 4 buttons for activating of scenarios 1,2,3 and 4. Scenarios can be customized by the Home+ Control app. Surface installation with repositionable stickers (supplied) or onto a flushmounting box. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules.</p>	<input type="checkbox"/> KW37M2 <input checked="" type="checkbox"/> KG37M2 <input type="checkbox"/> KM37M2	 Cover for item K4575CW

 **White** colour cover

 **Black** colour cover

 **Sand** colour cover

 **Neutral item (without cover)**

Items in red colour: New products



# Living Now with Netatmo smart electrical system - EUROPEAN VERSION

wireless controls and controls for energy management and gateway



4142PC




FC80CC



F20T60A



KG4141AC





K4500C




FC80GT

Devices to be completed with appropriate cover as indicated below

Item	Connected module for energy management	Item	Gateway
○ 4141PC	 <p>Connected Presa plug&amp;play socket. Directly connected to an existing socket, it allows remote control of all the connected electrical appliances. It also monitors the instantaneous, daily and monthly consumption. Compatible with all the devices with power up to 16 A 3680 W (with overload protection). It can be associated to wireless light controls. Power supply 110-230 V~</p>	○ K4500C	 <p>Gateway. This pack enables to create a connected installation in the home. It can be used to control lighting, roller shutters and electrical equipment plugged into connected sockets:</p> <ul style="list-style-type: none"> <li>- using your smartphone and the Home + Control app</li> <li>- using voice assistants</li> <li>- from the general control at the entrance to your home</li> </ul> <p>Supplied with the Home/Away wireless master switch required for the association procedure of all connected devices. Power supply 110-230 V~ - 2 modules</p>
○ 4142PC	 <p>As above French/belgian standard socket</p>	○ FC80GT	 <p>Gateway as above for DIN switchboard. Supplied without wireless In&amp;Out master scenario control item K4570CW. - 2.5 DIN modules.</p>
○ FC80CC	 <p>Connected contactor for single-phase and/or three-phase loads with maximum absorption In= 20 A. With meter for the measurement of the current absorbed by the load. Power supply 110-230 V~ - 1 DIN module</p>		
○ F20T60A	 <p>Connected DIN meter. It gives the possibility of measuring the energy consumptions of the whole home system (instantaneous, daily, monthly). It is also possible to receive notifications when the maximum power allowed by the contract with the energy supplier is reached, so that any blackouts may be avoided. A toroid for the current reading is provided. Power supply 110-230 VA - 1 DIN module</p>		
○ FC80GCS	 <p>Connected DIN load management module for the monitoring of the consumptions of the whole electric system, the powering or disconnection of the loads, and the setting of scenarios with priority or non-priority loads. When the maximum intended power is reached, the non-priority loads are temporarily disconnected to avoid black-outs. A toroid for the current reading is provided. Power supply 110-230 V~ - 1 DIN module</p>		
Item	Connected socket	Item	Cover required for the gateway
□ KW4141AC ■ KG4141AC □ KM4141AC	<p><b>Connected socket</b></p>  <p>2P+E 16 A 250 V a.c. German standard connected socket. It allows remote control of electric devices and also to monitor their consumption (instantaneous, daily, monthly). It is also possible to receive notifications that can be configured. Compatible with all the electric devices with power up to 16 A 3680W (with overload protection). Integrated with a 2-module support, it can be installed instead of an existing socket in a 40 mm deep box. Screw fixing and connection using automatic clamps. It has a blue LED that lights up when the socket is ON and that can be configured by means of the Home + Control APP. It can be associated to one or more wireless light controls. Power supply 110-230 V~</p> <p>As above French/belgian standard socket</p>	□ KW30M2 ■ KG30M2 □ KM30M2	<p><b>Cover required for the gateway</b></p> <p><b>2 modules</b></p>  <p>Cover for item K4500C in combination with the relative colored cover item KW40M2, KG40M2, KM40M2 and for item K4510C in combination with the relative colored cover item KW40, KG40, KM40.</p>
□ KW4142AC ■ KG4142AC □ KM4142AC		□ KW40M2 ■ KG40M2 □ KM40M2	<p><b>Cover for the gateway scenario control</b></p> <p><b>2 modules</b></p>  <p>Cover for item K4570CW (scenario control in the gateway item K4500C)</p>
		□ KW34M2 ■ KG34M2 □ KM34M2	<p><b>Cover for connected socket</b></p> <p><b>2 modules</b></p>  <p>Cover for item KW4141AC Cover for item KG4141AC Cover for item KM4141AC</p>
		□ KW35M2 ■ KG35M2 □ KM35M2	 <p>Cover for item KW4142AC Cover for item KG4142AC Cover for item KM4142AC</p>



KW4501C



KG4501C



KM4501C



KM51



KW34M2



KG35M2

## Item

KW4501C  
 KG4501C  
 KM4501C

**Gateway with socket**

The gateway creates a connected installation in the home. It can be used to control lights, shutters, and electric appliances plugged into connected sockets:  
 - using the smartphone and the Home + Control app  
 - using the voice assistants

- from the general control at the home entrance. It integrates a 2P+E 16 A 250 V~ German standard connected socket for the remote control of electric devices and to monitor their consumption (instantaneous, daily, monthly). Compatible with all the electric devices with power up to 16 A 3680W (with overload protection). It can be installed instead of an existing socket in a 40 mm deep box. Screw fixing and connection using automatic clamps  
 It has a blue LED that lights up when the socket is ON and that can be configured by means of the Home + Control APP. It can be associated to one or more wireless light controls. It is also supplied with wireless master IN&OUT scenario control, required for the association of all connected devices.  
 Power supply 110-230 V~

## Item

KW51  
 KG51  
 KM51

**Cover required for the gateway with socket****2 modules**

Cover required for all the gateways with sockets, in addition to the 2 modules cover for the socket part

**Cover for the socket****2 modules**

Cover for item KW4501C  
 Cover for item KG4501C  
 Cover for item KM4501C



Cover for item KW4502C  
 Cover for item KG4502C  
 Cover for item KM4502C

**EXAMPLE: FUNCTION, COVER PLATE & COVER COLOUR CHOICE**

①


KW4501C

+

②  
**KA4802M2KW**  
 (see the section "range of cover plates" for the other cover plate colors)




②



③

KW51

(covers available also colors black and sand)




+



④

**FINAL RESULT**



KW4502C

KG4502C

KM4502C



KW51

KW34M2

KG35M2

## Item

- KW4502C
- KG4502C
- KM4502C

**Gateway with socket**

The gateway creates a connected installation in the home. It can be used to control lights, shutters, and electric appliances plugged into connected sockets:

- using the smartphone and the Home + Control app
- using the voice assistants

- from the general control at the home entrance. It integrates a 2P+E 16 A 250 V~ French/belgian standard connected socket for the remote control of electric devices and to monitor their consumption (instantaneous, daily, monthly). Compatible with all the electric devices with power up to 16 A 3680W (with overload protection). It can be installed instead of an existing socket in a 40 mm deep box. Screw fixing and connection using automatic clamps

It has a blue LED that lights up when the socket is ON and that can be configured by means of the Home + Control APP. It can be associated to one or more wireless light controls. It is also supplied with wireless master IN&OUT scenario control, required for the association of all connected devices.

Power supply 110-230 V~

## Item

- KW51
- KG51
- KM51

**Cover required for the gateway with socket****2 modules**

Cover required for all the gateways with sockets, in addition to the 2 modules cover for the socket part

- KW34M2
- KG34M2
- KM34M2

- KW35M2
- KG35M2
- KM35M2

**Cover for the socket****2 modules**

Cover for item KW4501C  
Cover for item KG4501C  
Cover for item KM4501C



Cover for item KW4502C  
Cover for item KG4502C  
Cover for item KM4502C

## EXAMPLE: FUNCTION, COVER PLATE &amp; COVER COLOUR CHOICE

①

KW4502C

+

②

KA4802M2KW


(see the section "range of cover plates" for the other cover plate colors)



③


KW51

(covers available also colors black and sand)



+

KW35M2



④

FINAL RESULT





XW8002



XG8002



XM8002



XW8002W

The Smarter with Netatmo connected thermostat, together with the dedicated HOME+CONTROL APP, is a device which allows you to adjust and monitor the temperature in the rooms precisely and accurately; all the programming and most of the functions are performed simply and intuitively using the APP. Thanks to its Wi-Fi connection, Smarter with Netatmo can be programmed and controlled remotely; it can also display the temperature and humidity measured in the room. The temperature level can be set locally for manual operation and the Boost mode can be activated. The Boost forces the switching on of the system for a limited time (30, 60 or 90 minutes) independent of the measured and programmed temperature.

It's also possible to set a different temperature in each room of the house for the maximum comfort, thanks to its compatibility with Netatmo smart radiator valves.

Smarter with Netatmo can also be controlled with Google, Amazon Alexa and Apple Home Kit voice assistants.

#### Features:

- 110 ÷ 230 V~, 50/60 Hz power supply;
- 2 W max absorption;
- maximum cable section 1 x 1.5mm<sup>2</sup>;
- temperature measurement 5 ÷ 40°C;
- temperature set-point 5 ÷ 40°C;
- increase of 0.5°C;
- 1-contact output in switching free of potential 5(2)A.

#### Types of installation:

- flush mounted, on boxes item 503E or 500 (for item 500 use the wall dowels)
- plasterboard, on boxes 2 module and 3 module

It is available in three colours: white (XW8002), sand (XM8002) and black (XG8002).

Item	Connected thermostats
□ XW8002	White
■ XG8002	Black
□ XM8002	Sand
XW8002W	 <p>Features: as XW8002. Installation on the wall, using screws and dowels suitable for the installation surface (brickwork, plasterboard, tiles etc.). It is only available in white.</p>

**App HOME + CONTROL for management of connected devices**



Download on  
App Store

GET IT ON  
Google Play

works with  
Hey Google

Works with  
Apple HomeKit

WORKS WITH  
alexa

# Living Now



MyHOME\_Up system




MYHOMESERVER1



3488



3488W



3487



3487AP

<b>Item</b> <input type="radio"/> MYHOMESERVER1	<b>Control server using the app</b>  Server to associate devices during the system starting-up and for the local and remote management of the functions by the user with the specific MyHOME_Up application for Android and iOS smartphones or tablets.
<input type="radio"/> MH SERVER KIT	<b>MyHOME Server1 KIT</b>  Kit containing MyHOME Server1 and Access Point for communication between the MyHome_Up system to which it is connected, and a smartphone or tablet where the MyHome-Up App is installed.
<input type="radio"/> 3488 <input type="radio"/> 3488W	<b>HOMETOUCH - Touch screen 7"</b>  HOMETOUCH - Touch Screen 7" for the management of all MyHOME_Up functions, that can be integrated with the video door entry system and with indoor and outdoor Netatmo cameras, to be used as connected internal unit. To use the home automation functions, configuration is not necessary. It is possible to display the MyHOME_Up system status and control the integrated functions (lights, automation, scenarios, burglar alarm, temperature management, Nuvo music system, ...). Thanks to the "DOOR ENTRY for HOMETOUCH" application, available both for Android and iOS operating systems, it is also possible to manage the video door entry functions of a BTicino 2 wires system using the 7" capacitive display or the Smartphone. Flush mounted installation with box for masonry walls (item 3487) or wall mounted installation with the supplied metal bracket. Available in tech grey and in white.
<input type="radio"/> 3487	<b>Box for flush mounted installation</b>  Box for flush mounted installation of the HOMETOUCH Touch screen item 3488 and 3488W. Width 197 mm, height 148 mm and depth 52 mm.
<input type="radio"/> 3487AP	 Support for flush mounted installation on plasterboard walls of the HOMETOUCH Touch screen item 3488 and 3488W.
<b>Item</b> <input type="radio"/> F429	<b>SCS/DALI interface</b>  DALI dimmer, 8 independent outputs with maximum load 16 ballast at 230 Vac, pushbutton for load direct control - 6 DIN modules
<input type="radio"/> F459	<b>Driver manager</b>  Integration platform with other brand systems - 6 DIN modules Contact the BTicino System Integration Service to check the feasibility of specific integrations and to request the licence needed to use the Driver manager (Toll free number 800.837035)
	<b>App DOOR ENTRY for HOMETOUCH</b>  This allows the user to manage the video internal unit calls locally and remotely using the smartphone or with a simple touch open the gate, activate the cameras and the video door entry answering machine.
	<b>App MyHOME_Up</b>  Mobile device App that allows: - the installer, thanks to a self-learning procedure, to easily associate the devices together when starting up the system; - the user to manage his home home-automation wherever he is.





KG8013



K8003



KM8010




KW8011

K8002L  
K8002S

K8001



KGB100



KW8103

## Item

## Voice control

- KW8013
- KG8013
- KM8013

 Amazon Alexa digital control device with voice assistant, including two touch controls for lighting management.  
27 Vd.c. power supply from BUS through connection module item KW8001 or additional power supply unit, item K8003 - 3 modules

## Item

## Blanking module

- KW8100
- KG8100
- KM8100

 Cover for blanking module art. K4950  
- 1 module

## OK8003

## Power supply



Connection module with additional power supply dedicated to Voice control Alexa built-in item KW/KG/KM8013  
- 2 modules

- KW8010
- KG8010
- KM8010

## Light control



Touch control for the management of ON/OFF light functions. One single control can manage from 1 to 2 functions between single lights, light groups or general lights.  
- 1 module

## OK8102

## Electrified frame for 2 module box



Electrified frame with intermediate control separators (removable). For the installation of up to 3 digital controls or covers, item KW/KG/KM8100 in 2-module box with support K8102

- KW8011
- KG8011
- KM8011

## Full control



Touch control for the management from 1 to 3 functions between: lights on/off, load control, dimmer, shutters up/down with or without preset and scenarios. It can also be used as group or general control. It has on-board proximity sensor that allows the display of function icons/symbols when approaching the control - 1 module

## OK8002L

## ON/OFF actuators for lights and for shutters



Flush-mounted actuator with 2 independent and neutral relays for "zero crossing" function - single or double 230 V~ loads - 1 module

## OK8002S



Flush-mounted shutter actuator with 2 independent relays. It allows the management of a specific shutter position. Through the control KW/KG/KM8011, together with the UP/DOWN function monostable and bistable, the actuator also places the shutter in a stored (PRESET) position - 1 module

## OK8001

## Connection modules



Device for the power supply of controls and actuators through electrified frame item KW/KG/KM8103 KW/KG/KM8103P1 KW/KG/KM8104 KW/KG/KM8104P1 KW/KG/KM8102P1

- KW8103
- KG8103
- KM8103

- KW8103P1
- KG8103P1
- KM8103P1

- KW8104
- KG8104
- KM8104

- KW8104P1
- KG8104P1
- KM8104P



Electrified frame with intermediate control separators (removable). For the installation of up to 3 digital controls or covers, item KW/KG/KM8100 in 3-module box with support K4703



Electrified frame with intermediate control separators (removable). For the installation of up to 4 digital controls or covers, item KW/KG/KM8100 in 3-module box with support K4703



Electrified frame with intermediate control separators (removable). For the installation of up to 4 digital controls or covers, item KW/KG/KM8100 in 4-module box with support K4704



Electrified frame with intermediate control separators (removable). For the installation of up to 5 digital controls or covers, item KW/KG/KM8100 in 4-module box with support K4704



Devices to be completed with appropriate cover as indicated below

Item	Control devices	Item	Contact interface
OK4652M2	Control for the management of one or two ON/OFF functions, the shutter UP/DOWN function and the adjustment of a dimmer load. It can also be used as scenario control and for the call to the floor, staircase light switching on and door lock activation functions. It manages advanced shutter functions. - 2 modules. To be completed with 1 or 2-module covers.	O3477	Basic module control interface with 2 independent contacts for the control of 2 actuators for single function loads, or 1 actuator for double function loads (shutters) - the inputs accepts two traditional switches or pushbuttons with NO and NC contact, or a traditional two-way switch, or interlocked pushbuttons.
OK4652M3	Control for the management of up to three separate functions as described above - 3 modules. To be completed with 1 or 2-module covers.	OF428	As above - 2 DIN modules
OK4672M2L	Actuator/control with 2 independent relays for single or double loads: The device can be also configured to manage a remote actuator with the same functions of the K4652M2 and K4652M3 controls - 2 modules. To be completed with 1 or 2-module covers.	<b>Cover without symbols</b>	
OK4672M2S	Actuator/control for shutter Shutter actuator with 2 internal relay 2 A 250 V~. In addition to the monostable and bistable UP/DOWN function, the actuator also places the rolling shutter in a stored (PRESET) position. The device can be also configured to manage a remote actuator - 2 modules. To be completed with 1 or 2-module covers.	<b>1 module</b> <input type="checkbox"/> KW01 <input checked="" type="checkbox"/> KG01 <input type="checkbox"/> KM01  <input type="checkbox"/> KW01X <input checked="" type="checkbox"/> KG01X <input type="checkbox"/> KM01X	
		<input type="checkbox"/> KW01MH2 <input checked="" type="checkbox"/> KG01MH2 <input type="checkbox"/> KM01MH2  <input type="checkbox"/> KW01MH2X <input checked="" type="checkbox"/> KG01MH2X <input type="checkbox"/> KM01MH2X	
		Lightable cover for item K4652M2, K4652M3 and K4672M2L Lightable cover high brightness for item K4652M2, K4652M3 and K4672M2L	
		Lightable cover for item K4652M2 and K4672M2L Lightable cover high brightness for item K4652M2 and K4672M2L	

#### LOADS THAT CAN BE DRIVEN (230 V~ 50/60 Hz)

Actuators	Type
Energy saving incandescence and halogen lamps	LED lamps
K4672M2L	250 W Max 2 lamps
K4672M2S	-

**Notes:**

- 1) Power factor corrected fluorescent lamps, discharge lamps.
- 2) Account must be taken of the transformer yield to calculate the effective power of the load connected to the actuator. For example if a dimmer is connected to a 100 VA ferromagnetic transformer with yield 0.8, the effective power of the load will be 125 VA.
- 3) The transformer must be loaded at its rated power and however never less than 90% of this power. It is preferable to use a single transformer rather than several transformers in parallel. For example it is better to use a single 250 VA transformer with 5 50W spotlights connected rather than use 5 50 VA transformers in parallel each with a 50 W spotlight.
- 4) The symbol on the actuators refers to the shutter reducer motors.

 **White** colour cover

 **Black** colour cover

 **Sand** colour cover

 **Neutral item (without cover)**

Items in red colour: New products



Devices to be completed with appropriate cover as indicated below

Item	Cover with symbols	Item	Cover with symbols
<b>1 module</b>			<b>2 modules</b>
Lightable cover for item K4652M2, K4652M3 and K4672M2L			Lightable cover for item K4652M2 and K4672M2L
<input type="checkbox"/> KW01MHAG		<input type="checkbox"/> KW01MH2AG	
<input checked="" type="checkbox"/> KG01MHAG		<input checked="" type="checkbox"/> KG01MH2AG	
<input type="checkbox"/> KM01MHAG		<input type="checkbox"/> KM01MH2AG	
<input type="checkbox"/> KW19MH		<input type="checkbox"/> KW19MH2	
<input checked="" type="checkbox"/> KG19MH		<input checked="" type="checkbox"/> KG19MH2	
<input type="checkbox"/> KM19MH		<input type="checkbox"/> KM19MH2	
<input type="checkbox"/> KW01A		<input type="checkbox"/> KW01MH2A	
<input checked="" type="checkbox"/> KG01A		<input checked="" type="checkbox"/> KG01MH2A	
<input type="checkbox"/> KM01A		<input type="checkbox"/> KM01MH2A	
<input type="checkbox"/> KW01MHBED		<input type="checkbox"/> KW01MH2BED	
<input checked="" type="checkbox"/> KG01MHBED		<input checked="" type="checkbox"/> KG01MH2BED	
<input type="checkbox"/> KM01MHBED		<input type="checkbox"/> KM01MH2BED	
<input type="checkbox"/> KW01MHGEN		<input type="checkbox"/> KW01MH2GEN	
<input checked="" type="checkbox"/> KG01MHGEN		<input checked="" type="checkbox"/> KG01MH2GEN	
<input type="checkbox"/> KM01MHGEN		<input type="checkbox"/> KM01MH2GEN	
<input type="checkbox"/> KW01MHBACK		<input type="checkbox"/> KW01MH2BACK	
<input checked="" type="checkbox"/> KG01MHBACK		<input checked="" type="checkbox"/> KG01MH2BACK	
<input type="checkbox"/> KM01MHBACK		<input type="checkbox"/> KM01MH2BACK	
<input type="checkbox"/> KW01D		<input type="checkbox"/> KW01MH2D	
<input checked="" type="checkbox"/> KG01D		<input checked="" type="checkbox"/> KG01MH2D	
<input type="checkbox"/> KM01D		<input type="checkbox"/> KM01MH2D	
<input type="checkbox"/> KW01F		<input type="checkbox"/> KW01MH2F	
<input checked="" type="checkbox"/> KG01F		<input checked="" type="checkbox"/> KG01MH2F	
<input type="checkbox"/> KM01F		<input type="checkbox"/> KM01MH2F	
Lightable cover for item K4652M2, K4652M3 and K4672M2S			Lightable cover for item K4652M2 and K4672M2S
<input type="checkbox"/> KW05		<input type="checkbox"/> KW05MH2	
<input checked="" type="checkbox"/> KG05		<input checked="" type="checkbox"/> KG05MH2	
<input type="checkbox"/> KM05		<input type="checkbox"/> KM05MH2	
<input type="checkbox"/> KW06MH			
<input checked="" type="checkbox"/> KG06MH			
<input type="checkbox"/> KM06MH			

**White** colour cover

**Black** colour cover

**Sand** colour cover

Neutral item (without cover)

Items in red colour: New products



Item	Light control/actuator	Actuators for centralisations
○ 3476	1 relay actuator - for single loads: 2 A resistive or incandescence lamps, 2 A $\cos\phi$ 0.5 for ferromagnetic transformers - a traditional pushbutton with NO contact accepted in input	○ BMSW1003            ON/OFF actuator, 4 independent outputs with maximum load 16 A at 230 V a.c., clamp connection and RJ45, IP20 protection index, power supply 100/240 V a.c. 50/60 Hz, pushbuttons for load direct control - zero-crossing function - 6 DIN modules
OF411U2	Actuator with 2 independent relays – for single and double loads: 10 A resistive and 6 A incandescence lamps, 500 W for reducer motors, 2 A $\cos\phi$ 0.5 for ferromagnetic transformers and 250 W for fluorescent lamps - logic relay interlock via configuration - it has "Zero crossing" technology - 2 DIN modules	○ BMSW1005            ON/OFF actuator, "Zero Crossing" technology, 8 independent outputs with maximum load 16 A at 230 V a.c., clamp connection, IP20 protection index, power supply 100/240 V a.c. 50/60 Hz, pushbuttons for load direct control - 10 DIN modules
OF411/4	Actuator with 4 independent relays - for single, double or mixed loads: 2 A resistive, 2 A incandescence lamps, 500 W for reducer motors, 2 A $\cos\phi$ 0.5 for ferromagnetic transformers and 70 W for fluorescent lamps - logic relay interlock via configuration - 2 DIN modules	○ F401            Actuator with 2 internal relays and 4 pushbuttons. In addition to monostable and bistable UP/DOWN operation, the actuator also places the shutter in a stored (PRESET) position - 2 DIN modules

**LOADS THAT CAN BE DRIVEN (250 V~ 50/60 Hz)**

Actuators	Type						
3476	Energy saving incandescence and halogen lamps	LED lamps	Linear fluorescent lamps <sup>1)</sup>	Compact fluorescent lamps	Electronic transformers <sup>3)</sup>	Ferromagnetic transformers <sup>2) 3)</sup>	Reducer motors for shutters <sup>4)</sup>
411U2	2 A 460 W	40 W Max 1 lamp	- -	40 W Max 1 lamp	- -	2 A $\cos\phi$ 0.5 460 VA	- -
411/4	10 A 1380 W	250 W Max 4 lamps	4 A 230 W	250 W Max 4 lamps	4 A 230 W	4 A $\cos\phi$ 0.5 460 VA	2 A 460 W
BMSW1003	2 A 3680 W	70 W Max 2 lamps	0.3 A 70 W	70 W Max 2 lamps	0.3 A 70 W	2 A $\cos\phi$ 0.5 460 VA	2 A 460 W
BMSW1005	16 A 3680 W	2.1 A 500 VA	4.3 A	1150 W 5 A	16 A 3680 W	16 A 3680 W	- -
F401				1150 VA	16 A 3680 W	16 A 3680 W	2 A 250 V a.c.

**Notes:**

- 1) Power factor corrected fluorescent lamps, discharge lamps.
- 2) Account must be taken of the transformer yield to calculate the effective power of the load connected to the actuator. For example if a dimmer is connected to a 100 VA ferromagnetic transformer with yield 0.8, the effective power of the load will be 125 VA.
- 3) The transformer must be loaded at its rated power and however never less than 90% of this power. It is preferable to use a single transformer rather than several transformers in parallel. For example it is better to use a single 250 VA transformer with 5 50W spotlights connected rather than use 5 50 VA transformers in parallel each with a 50 W spotlight.
- 4) The symbol on the actuators refers to the shutter reducer motors.

 **White** colour cover

 **Black** colour cover

 **Sand** colour cover

 **Neutral item (without cover)**





Items in red colour: New products

 **Living Now MyHOME\_Up**  
dimmer actuators for lights, shutters and different loads



Item	Dimmers for centralisations	Item	Multi-load dimmers for centralisations
OF413N	 <p>1-output dimmer to supply fluorescent lamps or LED sources with input 1-10 V for single loads up to 2.5 A at 230 V a.c. – type of screw connection - power supply 27 Vd.c. – absorption 30 mA – max 10 ballast that can be connected (clamps 1-2) - with pushbutton for load direct control - version for fastening on DIN rail - 2 modules</p>	OF416U1	 <p>Multi-load dimmer, 1 output with maximum load 4.3 A at 230 V a.c., clamp connection and RJ45, IP20 protection index, power supply 100/240 V a.c. 50/60 Hz, pushbutton for load direct control - 6 DIN modules</p>
OBMDI1002	 <p>1/10V dimmer, "Zero Crossing" technology, 4 outputs with maximum load 4.3 A at 230 V a.c., clamp connection, IP20 protection index, power supply 100/240 V a.c. 50/60 Hz, pushbuttons for load direct control - 10 DIN modules</p>	OF418U2	 <p>Two-channel dimmer for the management of dimmer LEDs, dimmer compact fluorescent lamps (CFL), energy saving halogen lamps and electronic transformers at 110-230V. Possibility of parallelisation of the two channels to increase the maximum power which can be managed. power supply 27 Vd.c., absorption 18 mA - version for fastening on DIN rail - 4 modules</p>
OF429	 <p>DALI dimmer with 8 independent outputs for the connection of up to 16 DALI reactors for each output – 230 V a.c. power supply 50/60 Hz; 110 - 240 Vd.c. – absorption 5 mA - with pushbutton for load direct control - version for fastening on DIN rail - 6 modules</p>		

LOADS THAT CAN BE DRIVEN (230 V~ 50/60 Hz)

Actuators	Type						
							
Energy saving incandescence and halogen lamps	LED lamps	Linear fluorescent lamps <sup>1)</sup>	Compact fluorescent lamps	Electronic transformers <sup>3)</sup>	Ferromagnetic transformers <sup>2) 3)</sup>	Reducer motors for shutters <sup>4)</sup>	
Dimmer for ballast - 4 x 4.3 A outputs - 4x 1000VA@ 230 Vac - 4x500VA@ 230 Vac							
<b>F413N</b>	-	-	2 A 460 W <sup>5)</sup> Max 10 ballast, type T5, T8, compact or driver for LED	-	-	-	-
<b>F414</b>	0.25 - 4.3 A 60 - 1000 VA	-	-	-	-	0.25 - 4.3 A 60 - 1000 VA	-
<b>F416U1</b>	4.3 A 40 - 1000 W	-	-	-	4.3 A 40 - 1000 W	4.3 A 40 - 1000 W	-
<b>F418U2</b>	2x300 W	2x300 VA	-	2x300 VA	2x300 VA	2x300 VA	-
<b>F429</b>	SCS/DALI dimmer interface - 8 x16 ballast						

**Notes:**

- 1) Power factor corrected fluorescent lamps, discharge lamps. 2) Account must be taken of the transformer yield to calculate the effective power of the load connected to the actuator.  
For example if a dimmer is connected to a 100 VA ferromagnetic transformer with yield 0.8, the effective power of the load will be 125 VA.
- 3) The transformer must be loaded at its rated power and however never less than 90% of this power. It is preferable to use a single transformer rather than several transformers in parallel. For example it is better to use a single 250 VA transformer with 5 50W spotlights connected rather than use 5 50 VA transformers in parallel each with a 50 W spotlight.
- 4) The  symbol on the actuators refers to the shutter reducer motors.
- 5) Only compatible with lamps with 1/10 V ballast.

White colour cover

Black colour cover

Sand colour cover

Neutral item (without cover)

Items in red colour: New products



BMSE3003



048834



K4649



KW17



KG17



BMSO4001



BMSO4003



048971

048875

Devices to be completed with appropriate cover as indicated below

Item	Lighting/movement sensors	PIR passive infrared sensors
○ BMSE3001	<p>passive infrared SCS sensor for the detection of movement and the lighting level. Ceiling flush mounted installation using springs or installation boxes; surface installation using surface installation box, item 048875; IP20 protection index; RJ45 clamp connection; 8 m (50 m<sup>2</sup>) diameter coverage area for a 2.5 m installation height, maximum installation height 6 m; 27 V d.c. power supply from bus, absorption 12 mA; regulation with basic/advanced remote control (BMSO4003 and BMSO4001) or through configuration software, of the lighting level, from 5 to 1275 LUX, of the time delay, from 30 s to 255 h, and of the main operating parameters; Push&amp;Learn pushbutton</p>	<p>Green Switch: passive IR (PIR) sensor, suitable for the detection of presence in transit areas (corridors, toilets, service rooms). Operating mode (automatic or manual), time delay (5 s to 59min), and brightness threshold (20 to 1275 LUX) settable using the advanced/basic (BMSO4001/BMSO4003) configuration remote control; physical or virtual configuration. - 2 modules</p>
○ BMSE3003	<p>Double technology SCS sensor: passive infrared for the detection of presence and the lighting level. Ceiling flush mounted installation using springs or installation boxes; surface installation using surface installation box, item 048875; IP20 protection index; RJ45 clamp connection; 8 m diameter (50 m<sup>2</sup>) infrared coverage area for a 2.5 m installation height, 11 mm diameter (95 m<sup>2</sup>) ultrasound coverage area for a 2.5 m installation height, maximum installation height 6 m; 27 V d.c. power supply from BUS, absorption 17 mA; regulation with basic/advanced remote control (BMSO4003 and BMSO4001), or through configuration software, of the lighting level, from 5 to 1275 LUX, of the delay, from 30 s to 255 h, and of the main operating parameters; Push&amp;Learn pushbutton</p>	<p>Cover for K4659</p> <p>□ KW17 ■ KG17 □ KM17</p> <p>White Black Sand</p>
○ 048834	<p>IP55 passive IR (PIR) movement sensor, suitable for the detection of movement in outdoor or indoor transit areas (corridors, cellars, garage paths). Coverage area: 140° x 15 m at 2.5 m high. Operating mode (automatic or manual), time delay (5 s to 59min), and brightness threshold (20 to 1275 LUX) settable using the advanced/basic (BMSO4001/BMSO4003) configuration remote control; physical or virtual configuration. Wall or angular installation by means of accessory item 048971</p>	<p>Configuration remote controls</p> <p>○ BMSO4001</p> <p>○ BMSO4003</p> <p>The advanced configuration remote control, with IR transmitter and receiver, adjusts the main operating parameters of: Switch Sensor, Green Switch and SCS compatible sensors. With display for the acquisition of the parameters set on the sensors and to modify them. Batteries charged by USB mini port.</p> <p>The basic configuration remote control, with IR transmitter, adjusts the main operating parameters of: Switch Sensor, Green Switch and SCS compatible sensors. Modification of parameters only possible for preset values, battery recharge not available</p>
		<p>Installation accessories</p> <p>○ 048875</p> <p>○ 048971</p> <p>Ceiling mounted box compatible with the sensors: BMSE3001 and BMSE3003, IP20 protection index, dimensions Ø 100 x 50 mm</p> <p>Angle installation accessory, compatible with the 048834 accessory, IP42 protection index, dimensions (hxwd) 115 x 75 x 40 mm</p>

#### FEATURES OF THE LIGHTING/MOVEMENT SENSORS

SCS sensors	048834	BMSE3001	BMSE3003
Installation	wall mounted	ceiling flush mounted	
Type of operation	AUTO/ECO/WALKTHROUGH	AUTO/ECO/WALKTHROUGH	
Sensor technology	PIR	PIR	PIR+US
Power supply	27 V d.c. from Bus	27 V d.c. from Bus	
Protection index	IP55	IP20	
Coverage area at 2.5 m	15 m x 6 m	Ø 8 m	Ø 11 m
Coverage angles (v/h)	45°/140°	90/360°	
Lighting level	5 lux - 1275 lux	5 lux - 1275 lux	
Switching off delay	5 s - 59 min - 59 h	30 s - 255 h - 59 min - 59 sec	
Factory adjustments	300 lux - 15 min	300 lux - 15 min	
Connection type	SCS clamp	RJ45 connector	

White colour cover

Black colour cover

Sand colour cover

Neutral item (without cover)

Items in red colour: New products



KW4691



KG4691



KM4691



3454



F430/2



F430R8



F430V10

Devices to be completed with appropriate cover as indicated below

Item	<b>Thermostat</b>	<b>Probe without display</b>	<b>Accessories</b>	<b>Actuators</b>
□ KW4691	Probe with backlit display that controls the temperature of an individual zone. It features an input for the connection of a contact line (e.g. window contact). It can be used for the management of different types of systems, and the adjustment of the fan speed when fan coils are used. Possibility of automatic operation (summer/winter), with compatible systems - 2 modules	○ 3454	○ 3457	○ F430/2
■ KG4691	White	Temperature probe in basic module with wired sensor - to be associated to the temperature sensor item 3457 and Vantage probe item 8051	Temperature probe to be associated to the probe item 3454	○ F430/4
□ KM4691	Black			○ F430R8
	Sand			○ F430R3V10
				○ F430V10

□ **White** colour cover■ **Black** colour cover□ **Sand** colour cover

○ Neutral item (without cover)

Items in red colour: New products



Item	Consumption display	Item	Power supplies
OF520	Meter for the measurement of electricity on a maximum of 3 lines, by connecting 3 toroids to the appropriate inputs. Version for fastening on DIN rail - 1 module. The device is fitted with 1 toroid.	OE46ADCN	Power supply - input 230 Va.c. output 27 Vd.c. SELV - maximum absorbed current 450mA - installation on DIN profile for flush mounted or wall-mounted switchboards - 8 DIN modules
O3523	Additional electricity meter toroid, item F520 and for actuator with sensor, item F522 for the measurement of the earth leakage current. Cable length 400 mm.	OE49	Compact power supply - input 230 Va.c. - output 27 Vd.c. Maximum current delivered 600 mA - 2 DIN modules.
Item	Load control management	Item	Various accessories
OF521	Central unit for the management and control of the actuators of the load control system, to prevent the risk of detachment of the limiter of the electricity supplier. The central unit manages up to 63 loads, a contract power between 1.5 and 18 kW, and tolerance up to +/- 20%. It integrates an electricity meter for the controlled line. Version for fastening on DIN rail - 1 module. The device is fitted with 1 toroid.	O3515	spare removable clamp
OF522	Actuator with integrated current sensor for the measurement of the controlled load consumptions. 1 relay - 10 A for incandescence lamps and 4 A for fluorescent lamps or ferromagnetic transformers, and 500 for compact fluorescent and LED lamps - Bistable relay with zero crossing for the Automation and/or Load control management functions. Version for fastening on DIN rail - 1 module. Earth leakage control by connecting the additional toroid, item 3523.	O4669	Connection cables
OF523	1 relay actuator - for incandescence lamps and 4 A for fluorescent lamps or ferromagnetic transformers, and 500 W for compact fluorescent and LED lamps - bistable relay with zero crossing for the Automation and/or Load control management functions. Version for fastening on DIN rail - 1 module.	O4669/500	Sheathed pair made up of 2 flexible wires with unshielded plaited sheath - insulation 300/500 V - complies with standards CEI 46-5 and CEI 20-20 - coil length 100 metres
		O4669KM1	as above - in 500 m coils
		O336905	As above - reel lenght 1000 m (1)
		O336904	As above - low toxicity cable without halogens - ideal for application in environments where fire hazard safety is critical - coil length 200 metres
			Specific cable with 2 twisted conductors. It can be installed in underground piping, in accordance with standards (CEI 20-13 and CEI 20-14). It ensures the best performance in video systems (higher distance between EP and Handset when compared with other cables). 200 m coil
System	Cable		
	L4669 - L4669/500 L4669KM1 - 336905	336904	
Automation		•	•(1)
Energy Management/Consumption Display		•	•(1)
Temperature control		•	•(1)
Video door entry system			•
NOTE (1): for systems underground cable sections			

**Accessories**

O3508BUS removable clamp for BUS connection - width 3.81 mm



O3508U2 removable clamp 2 poles



O3508U3 removable clamp 3 poles



□ White colour cover


■ Black colour cover

□ Sand colour cover

O Neutral item (without cover)

Items in red colour: New products

## Living Now



## INSTALLATION AND COVER PLATE RANGE

**SELECTION TABLE**

	2 modules	2+2 modules	2+2+2 modules	2+2+2+2 modules
Flush mounted boxes	502E (70x70x50 mm)	502E (70x70x50 mm)	502E (70x70x50 mm)	502E (70x70x50 mm)
Plasterboard boxes	PB502N (Ø 71x50.5 mm)			
Supports	K4702 (*)	K4702 (*)	K4702 (*)	K4702 (*)
No. of function modules	2 modules	2+2 modules	2+2+2 modules	2+2+2+2 modules
Living Now cover plates	KA4802...(**)	KA4802M2...(**)	KA4802M3...(**)	KA4802M4...(**)
No. of 1-module covers required for the completion of the light point	2 covers	2+2 covers	2+2+2 covers	2+2+2+2 covers

Note: (\*) supplied without screws. Fastening using the screws supplied with boxes 502E and PB502N.

(\*\*) both horizontal and vertical installation



- Note: protective shell supplied with supports, available in all modularities.


To be used:

- at the site, before the installation of cover plates and covers
- after removing cover plates and covers when painting the walls


## Living Now

### installation examples


#### EXAMPLE OF INSTALLATION OF THE LIGHT POINT WITH 1-MODULE COVER








#### EXAMPLE OF LIGHT POINT COMPOSITION




\* Note: for solutions using one 2-module cover for the main controls, it will be necessary to use two "half-module blanking modules" (item K4949) at the sides of the control. (see the sample diagrams below)



**SELECTION TABLE**

	2 modules	3 modules	4 modules	6 modules
Flush mounted boxes	 <b>502E</b> (70x70x50 mm)	 <b>503E</b> (108x74x53.5 mm)	 <b>504E</b> (133x74x53.5 mm)	 <b>506L</b> (183.5x90x53.5 mm)
Plasterboard boxes	 <b>PB502N</b> (Ø 71x50.5 mm)	 <b>PB503N</b> (110x71x52 mm)	 <b>PB504N</b> (132.5x71x52 mm)	 <b>PB506N</b> (183x71x52 mm)
Supports	 <b>K4702</b> (*)	 K4703 with screws	 K4704 with screw	 K4706 with screw
No. of function modules	 2 modules	 3 modules	 4 modules	 6 modules
Living Now cover plates	 KA4802...	 KA4803...	 KA4804...	 KA4806...
No. of 1-module covers required for the completion of the light point	 2 covers	 3 covers	 4 covers	 6 covers

\* Note: supplied without screws. Fastening using the screws supplied with boxes 502E and PB502N.

**PROTECTED INSTALLATIONS**


- Note: protective shell supplied with supports, available in all modularities.

To be used:

- at the site, before the installation of cover plates and covers
- after removing cover plates and covers when painting the walls

## Living Now


### installation examples

#### EXAMPLE OF INSTALLATION OF THE LIGHT POINT WITH 1-MODULE COVER




#### EXAMPLE OF LIGHT POINT COMPOSITION


2 modules




3 modules



4 modules



6 modules



\* Note: for solutions using one 2-module cover for the main controls, it will be necessary to use two "half-module blanking modules" (item K4949) at the sides of the control. (see the sample diagrams below)

\*\* German standard socket centred on 3-module light point



2-module support

1 function with 1 module




2 half-module blanking modules item K4949

with 2 modules



3-module support

2 functions with 1 module



2 half-module blanking modules item K4949

1 cover with 2 modules 1 cover with 1 module



3-module support

1 function with 2 modules







2 half-module blanking modules item K4949

1 cover with 3 modules

**COMPOSITION OF DIGITAL CONTROLS**

For each type of box, the electrified frames used and the number of devices and the accessories that can be installed are indicated.

	2 modules	3 modules	4 modules		
Flush mounted boxes	 502E (70x70x50 mm)	 503E (108x74x53.5 mm)	 504E (133x74x53.5 mm)		
Plasterboard boxes	 PB502N (Ø 71x50,5 mm)	 PB503N (110x71x52 mm)	 PB504N (132.5x71x52 mm)		
Supports	 K8102	 K4703 with screws	 K4704 with screws		
Flush mounted boxes - connection module K8001; - actuators K8002L and e K8002S; - additional power supply K8003 (2 modules).	 3 modules		 4 modules		
Blanking module K4950	 max. 2 blanking modules		 max. 3 blanking modules		
Electrified frame	 3 modules ..8102P1	 3 modules ..8103	 3+1 modules ..8103P1	 4 modules ..8104	 4+1 modules ..8104P1
Voice control item ..8013 (3 modules)					
Digital control Light item ..8010 and Full item ..8011					
Cover for blanking module item 4950					

**WARNING FOR THE SELECTION OF THE DEVICES:**


1. Note (\*) The connection module is necessary; its position is free inside the box.
2. If the installation of the additional power supply, item K8003, is required for the voice command, item ..8013 (see the MyHOME\_Up guide for the details), connection module item K8001 must not be installed. The additional power supply (space required 2 modules) can only be installed in the electrified frame or together with 1 or 2 actuators, depending on the size of the box.

## Living Now

### installation examples


#### INSTALLATION EXAMPLE OF THE DIGITAL CONTROLS

##### Installation with flush-mounted actuator




Use in conjunction with the connection module, or another actuator, to take up the power voltage.

##### Installation with actuator in DIN switchboard



At the side of the connection module, install 2 false poles, item K4950, in any position.

##### Installation of the voice control



Remove the finishing bars from the electrified frame.  
When installing power supply item K8003, connection module item K8001 must not be used.

**Living Now**

european standard installation - range of cover plates - 2 module installation

WHITE



WHITE - **KW**  
(Material: techno polymer)



GOLD - **ZW**  
(Material: zamak)



MOON - **NW**  
(Material: zamak)

SAND




SAND - **KM**  
(Material: techno polymer)



COPPER - **ZM**  
(Material: zamak)



OAK - **LM**  
(Material: wood)




AURA - **DM**  
(Material: techno polymer)



OPTIC - **MM**  
(Material: techno polymer - pixel effect)

**Notes:**

- The cover plate/cover combinations shown in these pages are purely indicative. Each cover plate can in fact be combined with covers of any colours, as required by the customer (white, sand and black).
- The zamak and wood finishes are obtained using non-mass production procedures. The differences among the various cover plates are therefore a distinguishing valuable element.



### SELECTION TABLE

Finish	2 modules	2+2 modules	2+2+2 modules	2+2+2+2 modules
WHITE	KA4802KW	KA4802M2KW	KA4802M3KW	KA4802M4KW
GOLD	KA4802ZW	KA4802M2ZW	KA4802M3ZW	KA4802M4ZW
MOON	KA4802NW	KA4802M2NW	KA4802M3NW	KA4802M4NW
ICE	KA4802DW	KA4802M2DW	KA4802M3DW	KA4802M4DW
SKY	KA4802DA	KA4802M2DA	KA4802M3DA	KA4802M4DA
PIXEL	KA4802MW	KA4802M2MW	KA4802M3MW	KA4802M4MW
SAND	KA4802KM	KA4802M2KM	KA4802M3KM	KA4802M4KM
COPPER	KA4802ZM	KA4802M2ZM	KA4802M3ZM	KA4802M4ZM
OAK	KA4802LM	KA4802M2LM	KA4802M3LM	KA4802M4LM
AURA	KA4802DM	KA4802M2DM	KA4802M3DM	KA4802M4DM
OPTIC	KA4802MM	KA4802M2MM	KA4802M3MM	KA4802M4MM
BLACK	KA4802KG	KA4802M2KG	KA4802M3KG	KA4802M4KG
SPACE	KA4802NG	KA4802M2NG	KA4802M3NG	KA4802M4NG
STEEL	KA4802ZG	KA4802M2ZG	KA4802M3ZG	KA4802M4ZG
WALNUT	KA4802LG	KA4802M2LG	KA4802M3LG	KA4802M4LG
NIGHT	KA4802DG	KA4802M2DG	KA4802M3DG	KA4802M4DG
Supports	K4702	K4702 (x 2)	K4702 (x 3)	K4702 (x 4)

Items in red colour: New products

**Living Now****italian standard installation - range of cover plates - 1 module installation**

**WHITE - KW**  
(Material: techno polymer)

**GOLD - ZW**  
(Material: zamak)

**MOON - NW**  
(Material: zamak)



**ICE - DW**  
(Material: techno polymer)

**SKY - DA**  
(Material: techno polymer)

**PIXEL - MW**  
(Material: techno polymer - pixel effect)



**SAND - KM**  
(Material: techno polymer)

**COPPER - ZM**  
(Material: zamak)

**OAK - LM**  
(Material: wood)



**AURA - DM**  
(Material: techno polymer)

**OPTIC - MM**  
(Material: techno polymer - pixel effect)

**Notes:**

- The cover plate/cover combinations shown in these pages are purely indicative. Each cover plate can in fact be combined with covers of any colours, as required by the customer (white, sand and black).
- The zamak and wood finishes are obtained using non-mass production procedures. The differences among the various cover plates are therefore a distinguishing valuable element.




### SELECTION TABLE

Finish	2 modules	3 modules	4 modules	6 modules
WHITE	KA4802KW	KA4803KW	KA4804KW	KA4806KW
GOLD	KA4802ZW	KA4803ZW	KA4804ZW	KA4806ZW
MOON	KA4802NW	KA4803NW	KA4804NW	KA4806NW
ICE	KA4802DW	KA4803DW	KA4804DW	KA4806DW
SKY	KA4802DA	KA4803DA	KA4804DA	KA4806DA
PIXEL	KA4802MW	KA4803MW	KA4804MW	KA4806MW
SAND	KA4802KM	KA4803KM	KA4804KM	KA4806KM
COPPER	KA4802ZM	KA4803ZM	KA4804ZM	KA4806ZM
OAK	KA4802LM	KA4803LM	KA4804LM	KA4806LM
AURA	KA4802DM	KA4803DM	KA4804DM	KA4806DM
OPTIC	KA4802MM	KA4803MM	KA4804MM	KA4806MM
BLACK	KA4802KG	KA4803KG	KA4804KG	KA4806KG
SPACE	KA4802NG	KA4803NG	KA4804NG	KA4806NG
STEEL	KA4802ZG	KA4803ZG	KA4804ZG	KA4806ZG
WALNUT	KA4802LG	KA4803LG	KA4804LG	KA4806LG
NIGHT	KA4802DG	KA4803DG	KA4804DG	KA4806DG
Supports	K4702	K4703	K4704	K4706

Items in red colour: New products

Living Now




TECHNICAL INFORMATION,  
DIMENSIONAL DATA

## Living Now

### how to install the covers


#### LIGHT POINT INSTALLATION



#### REMOVING MOBILE COVERS




Mobile covers are those that move in relation to the light point, to allow the activation of a control (traditional, connected or MyHOME\_Up)




#### REMOVING FIXED COVERS




Fixed covers those are attached to the cover plates, such as for example blanking modules and all non-control devices (e.g. sockets, RJ connectors, TV sockets, USB chargers, etc.)





K4410  
K4411



Switch the light on and off and bring the light to the desired level with a simple soft touch.  
Possibility of setting different brightness levels.  
ON/OFF notification LED.

#### DIMMER ITEM K4410 - TABLE OF MANAGED LOADS

		1 - 10 V			
240 V ~ 50/60 Hz		Max.	600 VA	600 VA	600 VA
		Min.	20 VA	20 VA	20 VA

#### DIMMER ITEM K4411 - TABLE OF MANAGED LOADS

	R		L		C/L			
240 V ~ 50/60 Hz	Max.	400 W	400 W	400 VA	200 VA	400 VA	200 VA	75 W or max. 10 lamps
	Min.	3 W	3 W	3 VA	3 VA	3 VA	3 VA	3 W

# Living Now

## IR switches

### IR SENSOR ITEM K4430 - TABLE OF MANAGED LOADS




Table of managed loads

	+45°C +5°C	2 x 2,5mm <sup>2</sup>	Filament lamp or halogen lamp	LED	Fluorescent compact	Electronic transformer	Ferromagnetic transformer					
Loads			Max. 250 W Min. 3 W	1 A 0.02 A	Max. 100 W Min. 3 W	0.4 A 0.02 A	Max. 100 W Min. 3 W	0.4 A 0.02 A	Max. 250 W Min. 3 W	1 A 0.02 A	Max. 250 W Min. 3 W	1 A 0.02 A

### IR SENSOR ITEM K4432 - TABLE OF MANAGED LOADS






Table of managed loads


	+45°C +5°C	2 x 2,5mm <sup>2</sup>	Filament lamp or halogen lamp	LED	Fluorescent compact	Electronic transformer	Ferromagnetic transformer					
Loads			400 W	1.8 A	200 VA	0.8 A	200 VA	0.8 A	200 VA	0.8 A	200 VA	0.8 A

**IR SENSOR ITEM K4431 - TABLE OF MANAGED LOADS**


1. Switching off delay adjustment (\*)
2. Twilight adjustment (\*\*)
3. Connection clamps


**Table of managed loads**

	+45°C +5°C 2x2,5mm <sup>2</sup>	Filament lamp or halogen lamp	Electronic transformer	Fluorescent tube	Fluorescent compact or LED lamp	Motor (cos =0,5)
Loads		460 W	2 A	460 W	2 A	50 W
240 V ~ 50/60 Hz		460 W	2 A	460 W	2 A	0.5 A
		50 W	0.5 A	30 W	2 A	cos =0.5


**LED SAFETY LAMP< ITEM K4381 - AUTOMATIC OPERATION MODE SELECTION**

**Technical features**

Power supply	230 V a.c. , 50/60Hz
Consumption	2.5 VA (0.1 W)
Non-replaceable rechargeable battery	NiMH 3.6 V 140 mAh
Charging time	48 hours
Autonomy	2 hours
Maximum cable section	1 x 1.5 mm <sup>2</sup>
Light intensity	2400 mcd
Angle of emission	120°
Not pull-out	

# Living Now

## electronic thermostat


### ELECTRONIC ROOM THERMOSTAT ITEM KW4441-KG4441-KM4441




1. Backlit display
2. Temperature display
3. Lighting sensor
4. ON / OFF key  
sets the system (OFF) in anti-frost ( $7^{\circ}\text{C}$ ) or heat-protection ( $35^{\circ}\text{C}$ ) mode
5. Temperature setting indicator: appears when the temperature is being set
6. ON heating indicator
7. ON cooling indicator
8. Keys for temperature setting
9. OFF thermostat indicator
10. Connection clamps

#### Wiring diagrams


- System only for heating with clean contact (e.g. boiler activation) or heating and cooling with floor system



- Heating and cooling with different systems



- System only for heating with load to be controlled to the mains voltage (e.g. 230Vac solenoid valve)




#### Technical features

Power supply	110 – 240 V~, 50/60 Hz
Absorption	2 W max
Maximum cable section	1 x 1.5mm <sup>2</sup>
Operating temperatures	5 – 40 °C
Setpoint temperature	5 – 40 °C; increase of 0.5 °C
Type of operation	1BU
Pollution index	2
Rated pulse voltage	4 kV
Contact output	5[2] A

Technical features for all devices


Technology: ZigBee certified product, Zigbee 3.0 public profile  
 Performance: 200 m range in a free point-to-point field  
 Band frequency: from 2.4 to 2.4835 GHz

Connected TWO-WAY SWITCH ITEM K4003C



- 1 - Control pushbutton
- 2 - Setting pushbutton
- 3 - Notification LED
  - red steady: device not in Zigbee network
  - green steady: device in Zigbee network
- 4 - Connection clamps

Wiring diagram - interrupted



Wiring diagram - redirected or inverted





Table of managed loads

Loads	Filament lamp or halogen lamp	LED lamp	Fluorescent compact	Electronic transformer	Ferromagnetic transformer
240 V~ 50/60 Hz	250 W	50 W	125 VA	125 VA	125 VA
Technology	ZigBee certified product, Zigbee 3.0 public profile				
Performances	200 m range in a free point-to-point field.				
Power level	REC 70-03: <20dBm				
Band frequency	from 2,4 to 2,4835 GHz				

# Living Now


## dimmer

### DIMMER ITEM K/L/N/NT4411C




1 - Control pushbutton  
2 - Reset pushbutton  
3 - Notification LED  
4 - Connection clamps

#### Basic diagram



#### Diagram with remote control pushbuttons




#### Technical features

+45 °C 1 X 1,5 mm <sup>2</sup> 110 – 240 V~, 50/60 Hz		
---	--	--


Loads	Filament lamp or halogen lamp	LED lamp
240 VAC	150 W	150 W
100 VAC	75 W	75 W
Technology	Radio (Wireless meshed network)	
Power level	< 100 mW	
Band frequency	from 2,4 to 2,4835 GHz	

### SHUTTERS CONTROL ITEM K4027C



1 - Control pushbutton  
2 - Reset pushbutton  
3 - Notification LED  
4 - Connection clamps

#### Wiring diagram - interrupted




Warning: only compatible with standard motors  
(no pulse motors, no radio motors)

#### Technical features


+45 °C 1 X 1,5 mm <sup>2</sup> 110 – 240 V~, 50/60 Hz	
Loads	Motor for shutters
240 VAC max.	1 x 500 VA
100 VAC max.	1 x 270 VA
Technology	Radio (Wireless meshed network)
Power level	< 100 mW
Band frequency	from 2,4 to 2,4835 GHz

CONNECTED LIGHT RELAY ITEM 3584C



- 1 - Control pushbutton
- 2 - Setting pushbutton
- 3 - Notification LED
  - red steady: device not in Zigbee network
  - green steady: device in Zigbee network
- 4 - Connection clamps

Wiring diagram



Option: remote control through mechanical pushbutton, not luminous.


Table of managed loads

	R		L	
Loads	Filament lamp or halogen lamp	LED lamp	Fluorescent compact	Electronic transformer
240 V ~ 50/60 Hz	Max.	300 W	(*) 100 W	250 VA
				250 VA

\* or 10 maxi. lamps

\*\* warning: ferromagnetic transformers must be charged at over 60% of their rated power.

**CONNECTED MODULE FOR SOCKET ITEM K4531C**



1 - notification LED  
 - red steady: device not in Zigbee network  
 - green steady: device in Zigbee network  
 2 - Setting pushbutton  
 3 - Connection clamps  
 4 - load controlled phase cable

Wiring diagram






Table of managed loads

	+45°C +5°C	2x2,5mm <sup>2</sup>	Filament lamp	Halogen lamp	Electronic transformer	Ferromagnetic transformer	Fluorescent tube	Fluorescent compact	LED lamp	Ventilation motor
Loads										
230 V a.c. 3800 W cos 0,8	16 A									

**CONNECTED DIN METER ITEM F20T60A**




1 - Toroid connection  
 2 - notification LED  
 3 - Network association pushbutton




Wiring diagram

Living Now cover plates (3 module area system)

2-module cover plate




3-module cover plate



4-module cover plate




6-module cover plate




Living Now supports (3 module area system)


2-module support




3-module support



4-module support




6-module support




Living Now cover plates (2 module area system)


2-module cover plate




2+2-module cover plate



2+2+2-module cover plate





2+2+2+2-module cover plate




Living Now support (2 module area system)


2-module support



K4702 (x 2)




K4702 (x 3)




K4702 (x 4)

Living Now MyHOME\_Up electrified frames


3-module electrified frame




2-module support




3-module support




3+1-module electrified frame, 4 module



4-module support




4+1-module electrified frame




Smarther with Netatmo

flush mounted installation



plasterboard installation



XW8002 - XM8002 - XG8002

**BTicino** SpA  
Viale Borri, 231  
21100 Varese - Italy  
[www.bticino.com](http://www.bticino.com)

AD-EXLNW20C/GB – Edition 06/2020

BTicino S.p.A. reserves at any time the right to modify the contents of this booklet and to communicate, in any form and modality, the changes brought to the same.